

INDUSTRIAL COMPONENT DATA

15KV 7.5A LK 15XAB7.5 15XAB7-5 EATON ELECTRIC

Cartridge fuse, expulsion, MT, 7.5 A, AC 15 kV, 533 mm, ANSI,

..

Brand: EATON - MOELLER | Manufacturer Part Number: 15KV 7.5A LK



Manufacturer	EATON - MOELLER
MPN / Reference	15KV 7.5A LK
Catalog number	15XAB7-5
Category	Expulsion fuse-link, medium voltage
Minimum order	25 Pcs
Document ID	EO-B411CEDD8C
Generated	2026-08-06

Product Overview

Cartridge fuse, expulsion, MT, 7.5 A, AC 15 kV, 533 mm, ANSI, XA extra rapid
Ejection Fuse Cartridge, MT, 7.5 A, AC 15 kV, 533 mm, ANSI, XA extra rapid
15XAB7.5 - Expulsion fuse-link, medium voltage, 7.5 A, AC 15 kV, 533 mm, ANSI, XA extra rapid
Fuse, Expulsion fuse-link, medium voltage, 7.5 A, AC 15 kV, 533 mm, ANSI, XA extra rapid, fixed NEMA button head link, protection of transformer primary side, feeder, capacitor bank, ANSI C37-42, Breaking Capacity 8 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Bussmann fuses
--------------	----------------------------------

Additional Product Information

Expulsion fuse-link, medium voltage, 7.5 A, AC 15 kV, 533 mm, ANSI, XA extra rapid Fuse, Expulsion fuse-link, medium voltage, 7.5 A, AC 15 kV, 533 mm, ANSI, XA extra rapid, fixed NEMA button head link, protection of transformer primary side, feeder, capacitor bank, ANSI C37-42, Breaking Capacity 8 kA Delivery program
Product range Fuse Basic function Expulsion fuse-link Field of application medium voltage Rated current [I] 7.5 A Rated voltage AC 15 kV Size 533 mm Description fixed NEMA button head link Breaking Capacity 8 kA usable for size/applications protection of transformer primary side, feeder, capacitor bank Release characteristic [class] XA extra rapid Standard/Approval ANSI Standards/Regulations ANSI C37-42
ETIM for 15XAB7.5 Circuit breakers and fuses (EC003611)
Feature Name

Feature Value

Rated current (EF000227)

7.5 A

Rated voltage (EF000228)

15 kV

Voltage type (EF000187)

AC

Rated frequency (EF001663)

50 Hz

Release characteristic (EF000889)

Other

Type of termination (EF012540)

Fixed buttonhead

Standard (EF009322)

ANSI

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 15KV 7.5A LK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.