

INDUSTRIAL COMPONENT DATA

15KV 8A EXPULSION LINK 15TB8 EATON ELECTRIC

Cartridge fuse, expulsion, MT, 8 A, AC 15 kV, 533 mm, ANSI a, T ..

Brand: EATON - MOELLER | Manufacturer Part Number: 15KV 8A EXPULSION LINK



Manufacturer	EATON - MOELLER
MPN / Reference	15KV 8A EXPULSION LINK
Catalog number	15TB8
Category	Expulsion fuse-link, medium voltage
Minimum order	25 Pcs
Document ID	EO-C25F1A59C7
Generated	2026-08-06

Product Overview

Cartridge fuse, expulsion, MT, 8 A, AC 15 kV, 533 mm, ANSI a, T slow

15KV 8A EXPULSION LINK

Expulsion fuse-link, medium voltage, 8 A, AC 15 kV, 533 mm, ANSI, T slow

Fuse, Expulsion fuse-link, medium voltage, 8 A, AC 15 kV, 533 mm, ANSI, T slow, fixed NEMA button head link, protection of transformer primary side, feeder, capacitor bank, ANSI C37-42, Breaking Capacity 8 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Bussmann Series Medium Voltage fuses and accessories
--------------	--

Additional Product Information

General specifications

Product Name Eaton Bussmann series medium voltage expulsion fuse Catalog Number 15TB8 EAN 5027590436038

Product Length/Depth 225 mm Product Height 76 mm Product Width 106 mm Product Weight 18.96 g Certifications

ANSI/IEEE Std C37.42 Electrical data

Amperage Rating 8 A Voltage rating 15 kV Voltage type AC Current characteristic type Type T - Complies with ANSI C 37-42 requirements for slow acting T characteristics Rated frequency - min 50 Hz Product specification

Construction size 533 mm Standard ANSI Type of termination Fixed buttonhead Color Green

ETIM for 15TB8 Circuit breakers and fuses (EC003611)

Feature Name

Feature Value

Rated current (EF000227)

8 A

Rated voltage (EF000228)

15 kV

Voltage type (EF000187)

AC

Rated frequency (EF001663)

50 Hz

Release characteristic (EF000889)

T

Type of termination (EF012540)

Fixed buttonhead

Standard (EF009322)

ANSI

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 15KV 8A EXPULSION LINK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.