

INDUSTRIAL COMPONENT DATA

15KV 100A EXPULSION LINK 15SBR100 EATON ELECTRIC

Expulsion fuse-link, medium voltage, 100 A, AC 15 kV, 533 m..

Brand: EATON - MOELLER | Manufacturer Part Number: 15KV 100A EXPULSION LINK



Manufacturer	EATON - MOELLER
MPN / Reference	15KV 100A EXPULSION LINK
Catalog number	15SBR100
Category	Expulsion fuse-link, medium voltage
Minimum order	10 Pcs
Document ID	EO-4E97A79AA3
Generated	2026-08-06

Product Overview

Expulsion fuse-link, medium voltage, 100 A, AC 15 kV, 533 mm, ANSI, K fast, style BR termination

15KV 100A EXPULSION LINK

Fuse, Expulsion fuse-link, medium voltage, 100 A, AC 15 kV, 533 mm, ANSI, Solid link, fixed NEMA button head link with 1/4 inch UNF thread, protection of transformer primary side, feeder, capacitor bank, ANSI C37-42, Breaking Capacity 8 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Bussmann Series Medium Voltage fuses and accessories
--------------	--

Additional Product Information

General specifications

Product Name Eaton Bussmann series medium voltage expulsion fuse Catalog Number 15SBR100 EAN 5027590435802

Product Length/Depth 225 mm Product Height 76 mm Product Width 106 mm Product Weight 83.2 g Certifications

ANSI/IEEE Std C37.42 Electrical data

Amperage Rating 100 A Voltage rating 15 kV Voltage type AC Current characteristic type Type S - Solid links rated at 100A are also available in both button head and universal versions for fitting into expulsion fuse carriers where required. Rated frequency - min 50 Hz Product specification

Construction size 533 mm Standard ANSI Type of termination Removable buttonhead Color None

ETIM for 15SBR100 Circuit breakers and fuses (EC003611)

Feature Name

Feature Value

Rated current (EF000227)

100 A

Rated voltage (EF000228)

15 kV

Voltage type (EF000187)

AC

Rated frequency (EF001663)

50 Hz

Release characteristic (EF000889)

Other

Type of termination (EF012540)

Removable buttonhead

Standard (EF009322)

ANSI

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 15KV 100A EXPULSION LINK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.