

INDUSTRIAL COMPONENT DATA

1600AMP 250V AC SEMI-COND FWX-1600AH EATON ELECTRIC Microswitch, high speed, 5 A, AC 250 V, type T indicator..

Brand: EATON - MOELLER | Manufacturer Part Number: 1600AMP 250V AC SEMI-COND



Manufacturer	EATON - MOELLER
MPN / Reference	1600AMP 250V AC SEMI-COND
Catalog number	FWX1600AH
Category	HRC fuse
Minimum order	1 Pcs
Document ID	EO-203C3B61E3
Generated	2026-08-06

Product Overview

Microswitch, high speed, 5 A, AC 250 V, type T indicator, 6.3 x 0.8 lug dimensions, 000 to 3 with straight tags, 1mA-5A, 4V-250V

1600AMP 250V AC SEMI-COND

Fuse-link, high speed, 1600 A, AC 250 V, 200 kA, 48 x 89 mm, aR, UL

Fuse, Fuse-link, high speed, 1600 A, AC 250 V, 48 x 89 mm, UL, cylindrical with flush end contacts, DC common bus, DC drives, power converters/rectifiers and reduced voltage starters, UL, Breaking Capacity 200 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Bussmann Series High speed fuses
--------------	--

Additional Product Information

Fuse-link, high speed, 1600 A, AC 250 V, 200 kA, 48 x 89 mm, aR, UL
Fuse, Fuse-link, high speed, 1600 A, AC 250 V, 48 x 89 mm, UL, cylindrical with flush end contacts, DC common bus, DC drives, power converters/rectifiers and reduced voltage starters, UL, Breaking Capacity 200 kA
Delivery program

Product range FuseBasic function Fuse-linkField of application high speedRated current [I]_n 1600 ARated voltage AC 250 VSize 48 x 89 mmUtilization category aRBreaking Capacity 200 kAusable for size/applications DC common bus, DC drives, power converters/rectifiers and reduced voltage startersStandard/Approval ULShape cylindrical with flush end contactsStandards/Regulations ULTechnical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)Electric engineering, automation, process

control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (
[AFZ800015])Construction sizeOtherRated current1600 ARated voltage250 VVoltage typeACRated switching capacity200
kAUtilization categoryOtherType of fuse status indicatorNoneInsulated metal gripping lugs (IMGL)No
ETIM for FWX-1600AH Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

IEC 60269-4 flush end connections type B

Fuse construction type according to IEC 60269 (EF015865)

Other

Type of current (EF000143)

AC

Rated voltage AC (EF007682)

250 V

Rated current (EF000227)

15 A

Utilization category according to IEC 6026...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 1600AMP 250V AC SEMI-COND with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.