

INDUSTRIAL COMPONENT DATA

160A 690V AC TYPE T FUSE 160MT EATON ELECTRIC

Fuse-link, high speed, 160 A, AC 690 V, DC 350 V, BS88, 41 x 1..

Brand: EATON - MOELLER | Manufacturer Part Number: 160A 690V AC TYPE T FUSE



Manufacturer	EATON - MOELLER
MPN / Reference	160A 690V AC TYPE T FUSE
Catalog number	160MT
Category	HRC fuse
Minimum order	1 Pcs
Document ID	EO-A50470318B
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 160 A, AC 690 V, DC 350 V, BS88, 41 x 113 mm, aR, BS

160A 690V AC TYPE T FUSE

Eaton Bussmann series high speed British standard fuse, Single barrel, 160A, 690 VAC/350 VDC (IEC), 700 VAC (UL), Class aR, Breaking capacity 200 kA RMS Sym., 40 kA DC at 350 VDC (IEC)

Fuse, Fuse-link, high speed, 160 A, AC 690 V, DC 350 V, BS88, 41 x 113 mm, aR, BS, offset bolted tags, DC common bus, DC drives, power converters/rectifiers and reduced voltage starters, BS88-4, IEC 60269-4, Breaking Capacity 200 kA, Optional accessories fuse-holder BH-1133

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Bussmann Series High speed fuses
--------------	--

Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed british standard fuse Catalog Number 160MT EAN 5027590035415

UPC 051712831611 Product Length/Depth 46 mm Product Height 45 mm Product Width 115 mm Product Weight 256 g

Compliances CE Marked

RoHS Compliant Certifications UL Recognized

IEC Rated

Designed and tested to BS88 part 4

IEC 60269-4

UL recognized Product specifications

Type Fuse Application Semiconductor, DC Common bus, DC drives, power converters/rectifiers Amperage Rating 160 A Breaking capacity 200 kA Fuse indicator None Insulated metal gripping lugs (IMGL) No Utilization category aR (accompanied semiconductor protection) Voltage type AC/DC Rated switching capacity 200 kA Rated voltage AC 690 V Rated voltage DC 350 V Center-to-center distance of connections 84 mm Mounting dimension M8 Current type AC/DC Class Class aR Clearing (I₂T) 15000 at 415 V, 25000 at 660 V Watt losses 26 W Fuse shape Offset bolted tags Pre arc (I₂T) 2400 Color None Interrupt rating 200 kA RMS Sym (IEC/UL), 40 kA at 350 Vdc (IEC) Connection Blade end x blade end Construction size Other Mounting method Stud Packaging type Standard Voltage rating 690 V (IEC), 700 V (UL) Fuse type MT Suitable for MC-700 Trip indicator kit (indicator + clips)

TI700 Fuse indicator

MAI Microswitch/adaptor

MBI Microswitch/adaptor Fuse system (according to IEC 60269) Other

ETIM for 160MT Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Ot...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 160A 690V AC TYPE T FUSE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.