

INDUSTRIAL COMPONENT DATA

160A F/ PILLAR FUSE (10) 160MJ27-7 EATON ELECTRIC

Utility fuse-link, low voltage, 160 A, AC 415 V, BS88/J, 3..

Brand: EATON - MOELLER | Manufacturer Part Number: 160A F/ PILLAR FUSE (10)



Manufacturer	EATON - MOELLER
MPN / Reference	160A F/ PILLAR FUSE (10)
Catalog number	160MJ277
Category	HRC fuse
Minimum order	10 Pcs
Document ID	EO-8AD95394A9
Generated	2026-08-06

Product Overview

Utility fuse-link, low voltage, 160 A, AC 415 V, BS88/J, 31 x 112 mm, gL/gG, BS

Utility fuse cartridge, BT, 160 A, AC 415 V, BS88/J, 31 x 112 mm, gL/gG, BS

Fuse, Utility fuse-link, low voltage, 160 A, AC 415 V, BS88/J, 31 x 112 mm, gU, BS, dual bolted tags, 82 mm fixing centres, feeder pillars, BS88-2, IEC 60269-2, Breaking Capacity 80 kA, Optional accessories fuse-holder JW3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Busmann Series Low Voltage fuses and accessories
--------------	--

Additional Product Information

Utility fuse-link, low voltage, 160 A, AC 415 V, BS88/J, 31 x 112 mm, gL/gG, BS Fuse, Utility fuse-link, low voltage, 160 A, AC 415 V, BS88/J, 31 x 112 mm, gL/gG, BS, dual bolted tags, 82 mm fixing centres, feeder pillars, BS88-2, IEC 60269-2, Breaking Capacity 80 kA, Optional accessories fuse-holder JW3 [Delivery program

Product range Fuse Basic function Utility fuse-link Field of application low voltage Rated current [I] 160 A Rated voltage AC 415 V Construction size BS88/J Size 31 x 112 mm Utilization category gL/gG Description 82 mm fixing centres Breaking Capacity 80 kA usable for size/applications feeder pillars Standard/Approval BS Shape dual bolted tags Standards/Regulations BS88-2

IEC 60269-2 Optional accessories fuse-holder JW3 , Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse ()

[AFZ800015]) Construction size Other Rated current 160 A Rated voltage 415 V Voltage type AC Rated switching capacity 80 kA Utilization category gL/gG (cable protection/equipment protection) Type of fuse status indicator None Insulated metal

gripping lugs (IMGL) No]
ETIM for 160MJ27-7 Circuit breakers and fuses (EC004556)
Feature Name
Feature Value
Rated current (EF000227)
160 A
Utilization category according to IEC 60269 (EF002572)
Other
Breaking capacity (EF005617)
80 kA
Type of fuse....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 160A F/ PILLAR FUSE (10) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.