

INDUSTRIAL COMPONENT DATA

160A TYPE T FUSE (5) 160CEET PV-5A10/T EATON ELECTRIC cartridge fuse, ultra rapid, 160 A, AC 690 V, BS88, 20..

Brand: EATON - MOELLER | Manufacturer Part Number: 160A TYPE T FUSE (5)



Manufacturer	EATON - MOELLER
MPN / Reference	160A TYPE T FUSE (5)
Catalog number	PV-5A10/T
Category	HRC fuse
Minimum order	5 Pcs
Document ID	EO-AA296DCF3E
Generated	2026-08-06

Product Overview

cartridge fuse, ultra rapid, 160 A, AC 690 V, BS88, 20 x 37 x 139 mm, aR, BS
fuse cartridge, ultra fast, 160 A, AC 690 V, BS88, 20 x 37 x 139 mm, aR, BS
Fuse, Fuse-link, high speed, 160 A, AC 690 V, BS88, 20 x 37 x 139 mm, aR, BS, offset bolted tags (slotted), double barrel, 110 mm fixings, protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage starters, BS88-4, IEC 60269-4, Breaking Capacity 200 kA, Optional accessories fuse-block BH-1132

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series High speed fuses

Additional Product Information

cartridge fuse, high speed, 5 A, DC 1000 V, IEC 60269-6 type A, 10 x 59 mm, gPV, UL PV, IEC, UL Eaton catalogue No PV-5A10/T fuse, cartridge fuse, high speed, 5 A, DC 1000 V, IEC 60269-6 type A, 10 x 59 mm, gPV, UL PV, IEC, UL, cylindrical, with legs, non-centered fastening by bolt, protection of the strings of photovoltaic, IEC 60269-6, UL 2579, breaking capacity 50 kA [Range of delivery

Range fuse Basic function cartridge fuse Field of use high speed Rated current-job [I] Five Rated voltage of employment DC 1000 V Size IEC 60269-6 type A Zoom factor 10 x 59 mm Job class gPV

UL PV Power cut-off 50 kA Usable for size protection of the strings of photovoltaic Standard/Approval IEC

UL Form cylindrical with legs not centered to the mounting by bolt Standards/Regulations IEC 60269-6

UL 2579 , Technical data ETIM 7.0

Protective devices, facilities, equipment and people (EG000020) / Fuse, cylindrical (EC002704) Electricity, Electronics, Automation and Control / electrical Installation, switchgear / Insert fuse / Fuse cylindrical (security) ()

[AFZ797013]) size 10x38 mm rated voltage (Eu) 1000 - 1000 V rated voltage (Eu) other type of voltage DC type of voltage DC class of operation other operating frequency 0 - 0 Hz rated current Five with striker not characteristic trigger (type/curve) other power cut-off 50 kA]

ETIM for 160CEET Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse construction type according to IEC 60269 (EF015865)

Other

Rated c...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 160A TYPE T FUSE (5) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.