

INDUSTRIAL COMPONENT DATA

160A 690Vac TYPE T FUSE 160AEET EATON ELECTRIC cartridge fuse, ultra rapid, 160 a, AC 690 V, BS88, 20 x 36 x..

Brand: EATON - MOELLER | Manufacturer Part Number: 160A 690Vac TYPE T FUSE



Manufacturer	EATON - MOELLER
MPN / Reference	160A 690Vac TYPE T FUSE
Catalog number	160AEET
Category	HRC fuse
Minimum order	5 Pcs
Document ID	EO-7C8B451D2C
Generated	2026-08-06

Product Overview

cartridge fuse, ultra rapid, 160 a, AC 690 V, BS88, 20 x 36 x 102 mm, aR, BS

160A 690Vac TYPE T FUSE

Eaton Bussmann series high speed British standard fuse, Double barrel, Slotted bolted tags, 160A, 690 VAC/500 VDC (IEC), 700 VAC/500 VDC (UL), Class aR, Breaking capacity 200 kA RMS Sym., 50 kA DC at 500 VDC

Fuse, Fuse-link, high speed, 160 A, AC 690 V, BS88, 20 x 36 x 102 mm, aR, BS, offset bolted tags (slotted), double barrel, 80 mm fixing centres, protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage starters, BS88-4, IEC 60269-4, Breaking Capacity 200 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series High speed fuses

Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed british standard fuse Catalog Number 160AEET EAN 5027590436885

Product Length/Depth 110 mm Product Height 38 mm Product Width 100 mm Product Weight 99.6 g Compliances CE

Product specifications

Type Fuse Application Semiconductor, DC Common bus, DC drives, power converters/rectifiers Amperage Rating 160 A

Breaking capacity 200 kA Fuse indicator None Insulated metal gripping lugs (IMGL) No Utilization category aR

(accompanied semiconductor protection) Voltage type AC/DC Rated switching capacity 200 kA Rated voltage AC 690 V

Rated voltage DC 500 V Center-to-center distance of connections 80 mm Mounting dimension M8 Current type AC/DC

Class Class aR Watt losses 39 W Fuse shape Offset dual barrel slotted bolted tags Color None Interrupt rating 200 kA RMS

Sym, 50 kA at 500 Vdc Connection Blade end x blade end Construction size Other Mounting method Stud Voltage rating
690 V (IEC), 700 V (UL) Fuse type EET
AEET Suitable for EC-600 Trip indicator kit (indicator + clips)
TI700 Fuse indicator
MAI Microswitch/adaptor
MBI Microswitch/adaptor Fuse system (according to IEC 60269) Other
ETIM for 160AEET Circuit breakers and fuses (EC004556)
Feature Name
Feature Value
Fuse system according to IEC 60269 (EF017676)
Other
Fuse construction type according to IEC 60269 (EF015865)
Other
Type of current (EF000143)
AC/DC
Rated voltage AC (EF007682)
690 V
Rated voltage DC (EF012281)
500 V
Rated current (EF000227)
160 A
Utilization....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 160A 690Vac TYPE T FUSE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.