

INDUSTRIAL COMPONENT DATA

160A 240V AC BS88 FUSE 160LMT EATON ELECTRIC

Fuse-link, high speed, 160 A, AC 240 V, DC 150 V, BS88, 38 x 84..

Brand: EATON - MOELLER | Manufacturer Part Number: 160A 240V AC BS88 FUSE



Manufacturer	EATON - MOELLER
MPN / Reference	160A 240V AC BS88 FUSE
Catalog number	160LMT
Category	HRC fuse
Minimum order	1 Pcs
Document ID	EO-EA47AC4E54
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 160 A, AC 240 V, DC 150 V, BS88, 38 x 84 mm, aR, BS

160A 240V AC BS88 FUSE

Eaton Bussmann series high speed British standard fuse, Single barrel, 160A, 240 VAC/150 VDC (IEC), 250 VAC/150 VDC (UL), Class aR, Breaking capacity 200 kA RMS Sym., 40 kA DC at 150 VDC (IEC). 50 kA at 150 VDC (UL)

Fuse, Fuse-link, high speed, 160 A, AC 240 V, DC 150 V, BS88, 38 x 84 mm, aR, BS, offset bolted tags, protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage starters, BS88-4, IEC 60269-4, Breaking Capacity 200 kA, Optional accessories fuse-holder BH-0111

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series High speed fuses

Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed british standard fuse Catalog Number 160LMT EAN 5027590035347

UPC 051712831604 Product Length/Depth 84 mm Product Height 41 mm Product Width 39 mm Product Weight 180 g

Compliances CE Marked

RoHS Compliant Certifications UL Recognized

IEC Rated

Designed and tested to BS88 part 4

UL recognized

IEC 60269-4

CCC Product specifications

Type Fuse Application Semiconductor, DC Common bus, DC drives, power converters/rectifiers Amperage Rating 160 A
Breaking capacity 200 kA Fuse indicator None Insulated metal gripping lugs (IMGL) No Utilization category aR
(accompanied semiconductor protection) Voltage type AC/DC Rated switching capacity 200 kA Rated voltage AC 240 V
Rated voltage DC 150 V Center-to-center distance of connections 58.2 mm Mounting dimension M10 Current type AC/DC
Class Class aR Clearing (I₂T) 16000 Watt losses 17 W Fuse shape Offset bolted tags Pre arc (I₂T) 1100 Color None
Interrupt rating 200 kA RMS Sym, 40 kA at 150 Vdc (IEC)
200 kA RMS Sym, 50 kA at 150 Vdc (UL) Connection Blade end x blade end Construction size Other Mounting method
Stud Packaging type Standard Voltage rating 240 Vac, 150 Vdc Fuse type LMT Suitable for MC-250 Trip indicator kit
(indicator + clips)

TI250 Fuse indicator

MAI Microswitch/adaptor

MBI Microswitch/adaptor Fuse system (according to IEC 60269) Other

ETIM for 160LMT Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF0176...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 160A 240V AC BS88 FUSE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.