

INDUSTRIAL COMPONENT DATA

167806 Y7-167806 EATON ELECTRIC DOL starter, 0.3-1.2A, protection electronic, standard

Brand: EATON - MOELLER | Manufacturer Part Number: 167806



Manufacturer	EATON - MOELLER
MPN / Reference	167806
Catalog number	Y7-167806
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-F40CA6595E
Generated	2026-08-06

Product Overview

MSC-DE-1,2-M17-SP(220V50HZ,240V60HZ)

DOL starter, Ir= 0.3 - 1.2 A, 220 V 50 Hz, 240 V 60 Hz, AC voltage

DOL starter, Basic device: MSC, Setting range of overload releases: Ir= 0.3 - 1.2 A, Actuating voltage: 220 V 50 Hz, 240 V 60 Hz, AC voltage, Standards: IEC/EN 60947-4-1, VDE 0660, UL, CSA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Electronic Circuit Breakers

Additional Product Information

General specifications

Product Name Eaton Moeller® series MSC-DE DOL starter Catalog Number 167806 Model Code

MSC-DE-1,2-M17-SP(220V50HZ,240V60HZ) EAN 4015081643851 Product Length/Depth 145 mm Product Height 272 mm

Product Width 45 mm Product Weight 1.174 kg Certifications CSA-C22.2 No. 14-10

UL

IEC/EN 60947-4-1

UL Category Control No.: NKJH

UL60947-4-1A

CE

UL File No.: E123500

CSA

CSA Class No.: 3211-08

VDE 0660

CSA File No.: 012528 Features & Functions

Fitted with: Short-circuit release Functions Temperature compensated overload protection General

Class Adjustable Connection Screw terminals Connection to SmartWire-DT No Current flow times - min For all combinations with an SWD activation, you need not adhere to the minimum current flow times and minimum cut-out periods.

900 (Class 15) AC-4 cycle operation, Main conducting paths

1000 (Class 20) AC-4 cycle operation, Main conducting paths

700 (Class 10) AC-4 cycle operation, Main conducting paths

Note: Going below the minimum current flow time can cause overheating of the load (motor).

500 (Class 5) AC-4 cycle operation, Main conducting paths Cut-out periods - min ≤ 500 ms, main conducting paths, AC-4 cycle operation Degree of protection IP20

NEMA Other Model UL Type E starter Mounting method DIN rail Number of auxiliary contacts (normally closed contacts) 0

Number of auxiliary contacts (normally open contacts) 1 Overload release current setting - min 0.3 A Overload release current setting - max 1.2 A Overvoltage category II...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 167806 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.