

INDUSTRIAL COMPONENT DATA

167807 Y7-167807 EATON ELECTRIC DOL starter, 1-4A, protection electronic, standard

Brand: EATON - MOELLER | Manufacturer Part Number: 167807



Manufacturer	EATON - MOELLER
MPN / Reference	167807
Catalog number	Y7-167807
Category	Motor starter/Motor starter combination
Minimum order	1 Pcs
Document ID	EO-BBFEA5011E
Generated	2026-08-06

Product Overview

MSC-DE-4-M17-SP(220V50HZ,240V60HZ)

DOL starter, Ir= 1 - 4 A, 220 V 50 Hz, 240 V 60 Hz, AC voltage

DOL starter, Basic device: MSC, Setting range of overload releases: Ir= 1 - 4 A, Actuating voltage: 220 V 50 Hz, 240 V 60 Hz, AC voltage, Standards: IEC/EN 60947-4-1, VDE 0660, UL, CSA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Electronic Circuit Breakers

Additional Product Information

DOL starter, Ir= 1 - 4 A, 220 V 50 Hz, 240 V 60 Hz, AC voltageDOL starter, Basic device: MSC, Setting range of overload releases: Ir= 1 - 4 A, Actuating voltage: 220 V 50 Hz, 240 V 60 Hz, AC voltage, Standards: IEC/EN 60947-4-1, VDE 0660, UL, CSA

General specificationsProduct nameEaton Moeller® series MSC-DE Starter with electronic trip unitPart no.MSC-DE-4-M17-SP(220V50HZ,240V60HZ)EAN4015081643868Product Length/Depth145 millimetreProduct height272 millimetreProduct width45 millimetreProduct weight1.174 kilogramCertificationsCE

CSA

UL60947-4-1A

CSA-C22.2 No. 14-10

VDE 0660

UL

CSA File No.: 012528

UL File No.: E123500

IEC/EN 60947-4-1

UL Category Control No.: NKJH

CSA Class No.: 3211-08Product TradenameMSC-DEProduct TypeStarter with electronic trip unitProduct Sub TypeNoneFeatures & FunctionsFitted with:Short-circuit releaseFunctionsTemperature compensated overload protectionGeneral informationClassAdjustableConnectionScrew terminalsConnection to SmartWire-DTNoCurrent flow times - min500 (Class 5) AC-4 cycle operation, Main conducting paths

900 (Class 15) AC-4 cycle operation, Main conducting paths

For all combinations with an SWD activation, you need not adhere to the minimum current flow times and minimum cut-out periods.

700 (Class 10) AC-4 cycle operation, Main conducting paths

1000 (Class 20) AC-4 cycle operation, Main conducting paths

Note: Going below the minimum current flow time can cause overheating of the load (motor).Cut-out periods - min<= 500 ms, main conducting....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 167807 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.