

INDUSTRIAL COMPONENT DATA

16A 240V AC TYPE T FUSE (10) 16LET EATON ELECTRIC cartridge fuse, ultra rapid, 16 A, AC 240 V, DC 150 V, BS8..

Brand: EATON - MOELLER | Manufacturer Part Number: 16A 240V AC TYPE T FUSE (10)



Manufacturer	EATON - MOELLER
MPN / Reference	16A 240V AC TYPE T FUSE (10)
Catalog number	16LET
Category	HRC fuse
Minimum order	10 Pcs
Document ID	EO-C1D307ED67
Generated	2026-08-06

Product Overview

cartridge fuse, ultra rapid, 16 A, AC 240 V, DC 150 V, BS88, 18 x 56 mm, aR, BS

16A 240V AC TYPE T FUSE(10)

Eaton Bussmann series high speed British standard fuse, 16A, 280 VAC/150 VDC (UL), Class aR, Breaking capacity 200 kA RMS Sym., 50 kA DC at 150 VDC

Fuse, Fuse-link, high speed, 16 A, AC 240 V, DC 150 V, BS88, 18 x 56 mm, aR, BS, offset bolted tags, protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage starters, BS88-4, IEC 60269-4, Breaking Capacity 200 kA, Optional accessories fuse-holder BH-0111

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Bussmann Series High speed fuses
--------------	--

Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed british standard fuse Catalog Number 16LET Model Code 16A 240V AC TYPE T FUSE (10) EAN 5027590437660 UPC 051712831765 Product Length/Depth 55 mm Product Height 18 mm

Product Width 18 mm Product Weight 32 g Compliances RoHS Compliant

CE Marked Product specifications

Type Fuse Application Semiconductor, DC Common bus, DC drives, power converters/rectifiers Amperage Rating 16 A Breaking capacity 200 kA Fuse indicator None Insulated metal gripping lugs (IMGL) No Utilization category aR (accompanied semiconductor protection) Voltage type AC/DC Rated switching capacity 200 kA Rated voltage AC 280 V Rated voltage DC 150 V Center-to-center distance of connections 41.5 mm Mounting dimension M6 Current type AC/DC

Class Class aR Clearing (I2T) 70 at 120 V, 140 at 240 V Watt losses 2.5 W Fuse shape Offset bolted tags Pre arc (I2T) 15
Color None Interrupt rating 200 kA RMS Sym, 50 kA DC at 150 Vdc Connection Blade end x blade end Construction size
Other Mounting method Stud Packaging type Standard Voltage rating 280 V Fuse type LET Suitable for TI500 Fuse
indicator

MAI Microswitch/adaptor

MBI Microswitch/adaptor Fuse system (according to IEC 60269) Other

ETIM for 16LET Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Other

Fuse construction type according to IEC 60269 (EF015865)

Other

Type of current (EF000143)

AC/DC

Rated voltage AC (EF007682)

280 V

Rated vo...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 16A 240V AC TYPE T FUSE (10) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.