

INDUSTRIAL COMPONENT DATA

16AMP 240V AC BS88 FUSE 16LCT EATON ELECTRIC

Fuse-link, high speed, 12 A, AC 240 V, BS88, 18 x 56 mm, aR, BS

Brand: EATON - MOELLER | Manufacturer Part Number: 16AMP 240V AC BS88 FUSE



Manufacturer	EATON - MOELLER
MPN / Reference	16AMP 240V AC BS88 FUSE
Catalog number	16LCT
Category	HRC fuse
Minimum order	20 Pcs
Document ID	EO-95CA5359FF
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 12 A, AC 240 V, BS88, 18 x 56 mm, aR, BS

16AMP 240V AC BS88 FUSE

Eaton Bussmann series high speed British standard fuse, 16A, 240 VAC/150 VDC (IEC), 250 VAC/150 VDC (UL), Class aR, 200 kA RMS Sym.

Fuse, Fuse-link, high speed, 16 A, AC 240 V, DC 150 V, BS88, 9 x 47 mm, aR, BS, offset bolted tags, protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage starters, BS88-4, IEC 60269-4, Breaking Capacity 200 kA, Optional accessories fuse-holder BH-0111

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series High speed fuses

Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed british standard fuse Catalog Number 16LCT EAN 5027590437653 UPC 051712831758 Product Length/Depth 47 mm Product Height 9 mm Product Width 9 mm Product Weight 5.8 g Compliances CE Marked

RoHS Compliant Certifications UL Recognized

IEC Rated

Designed and tested to BS88 part 4

UL recognized

IEC 60269-4

CCC Product specifications

Type Fuse Application Semiconductor, DC Common bus, DC drives, power converters/rectifiers Amperage Rating 16 A
Breaking capacity 200 kA Fuse indicator None Insulated metal gripping lugs (IMGL) No Utilization category aR
(accompanied semiconductor protection) Voltage type AC/DC Rated switching capacity 200 kA Rated voltage AC 240 V
Rated voltage DC 150 V Center-to-center distance of connections 37.5 mm Mounting dimension M6 Current type AC/DC
Class Class aR Clearing (I2T) 100 Watt losses 2.5 W Fuse shape Offset bolted tags Pre arc (I2T) 20 Color None Interrupt
rating 200 kA RMS Sym, 50 kA DC at 150 Vdc Connection Blade end x blade end Construction size Other Mounting
method Stud Packaging type Standard Voltage rating 240 Vac, 150 Vdc Fuse type LCT Suitable for TI250 Fuse indicator
MAI Microswitch/adaptor

MBI Microswitch/adaptor Fuse system (according to IEC 60269) Other

ETIM for 16LCT Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Other

Fuse construction type according to IEC 60269 (EF015865)

Other

Type of current (EF0001...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 16AMP 240V AC BS88 FUSE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.