

INDUSTRIAL COMPONENT DATA

170M2045 FUSE 600A 2000VDC 2+/A173 PDST AR EATON ELECTRIC Fuse-link, high speed, 600 A, DC 2000 V, 65 x 164 ..

Brand: EATON - MOELLER | Manufacturer Part Number: 170M2045



Manufacturer	EATON - MOELLER
MPN / Reference	170M2045
Catalog number	FUSE 600A 2000VDC 2+/A173 PDST AR
Category	HRC fuse
Minimum order	1 Pcs
Document ID	EO-8411636A83
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 600 A, DC 2000 V, 65 x 164 x 216 mm, aR, IEC, with indicator

FUSE 600A 2000VDC 2+/A173 PDST AR

Fuse, Fuse-link, high speed, 600 A, DC 2000 V, 65 x 164 x 216 mm, aR, IEC, with indicator, square body with parallel bolted tags, dual-barrel, indicator style K for microswitch, traction, third rail, IEC 60269-4, Breaking Capacity 100 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Bussmann Series High speed fuses
--------------	--

Additional Product Information

Fuse-link, high speed, 600 A, DC 2000 V, 65 x 164 x 216 mm, aR, IEC, with indicator Fuse, Fuse-link, high speed, 600 A, DC 2000 V, 65 x 164 x 216 mm, aR, IEC, with indicator, square body with parallel bolted tags, dual-barrel, indicator style K for microswitch, traction, third rail, IEC 60269-4, Breaking Capacity 100 kA

General specifications Product name Eaton Bussmann series high speed traction fuse Part

no. 170M2045 EAN 5027590303859 Product Length/Depth 217 millimetre Product height 89 millimetre Product width 164 millimetre Product weight 4612 gram Compliances RoHS Compliant

Not Applicable Certifications IEC Rated Product Tradename None Product Type High speed traction fuse Product Sub

Type None Electrical data Amperage Rating 600 A Voltage rating 2000 V Interrupt rating 100 kA IEC Class Class aR Clearing (I2T) 289796 at 2000 Vdc Product specifications Application traction

third rail Fuse indicator Other Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) ()

[BAB264011])Fuse construction type according to IEC 60269OtherType of currentDCRated voltage ACVRated voltage DC2,000 VRated current600 AUtilization categoryaR (accompanied semiconductor protection)Breaking capacity100 kAColour codeNoneType of fuse status indicatorOtherPower loss at rated current305 WMounting holesM8Centre-to-centre distance of connections194 mm...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 170M2045 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.