

INDUSTRIAL COMPONENT DATA

172961 Y7-172961 EATON ELECTRIC SUVA safety switches,32 A, STOP function, Lockable in position 0 with cover ..

Brand: EATON - MOELLER | Manufacturer Part Number: 172961



Manufacturer	EATON - MOELLER
MPN / Reference	172961
Catalog number	Y7-172961
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-2959528724
Generated	2026-08-06

Product Overview

T3-2-2092CH/I2/SVB-SW-SI-CHF-230V

Eaton Moeller® series T3 SUVA safety switches, T3, 32 A, surface mounting, 2 N/O, 2 N/C, STOP function, with warning label „Interrupteur de sécurité“, Indicator light 230 V

SUVA safety switch, Product range: SUVA safety switches, Part group reference: T3, Stop Function: STOP function, With black rotary handle and locking ring, Notes: with warning label „Interrupteur de sécurité“, Information about equipment supplied: Indicator light 230 V, Locking facility: Lockable in position 0 with cover interlock, Degree of Protection: IP65, Design: surface mounting, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: I_u = 32 A, 2 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T3 SUVA safety switch Catalog Number 172961 Model Code

T3-2-2092CH/I2/SVB-SW-SI-CHF-230V EAN 4015081695492 Product Length/Depth 185 mm Product Height 124 mm

Product Width 108 mm Product Weight 0.5 kg Certifications IEC/EN 60947

VDE 0660

IEC/EN 60947-3

IEC/EN 60204 Catalog Notes Rated Short-time Withstand Current (I_{cw}) for a time of 1 second

ETIM for 172961 Low-voltage industrial controls and switchgear (EC000216)

Feature Name	
Feature Value	
Version as main switch (EF006981)	
Yes	
Version as maintenance-/service switch (EF006986)	
No	
Version as safety switch (EF006985)	
Yes	
Version as emergency stop installation (EF006959)	
No	
Version as reversing switch (EF009408)	
No	
Number of switches (EF005586)	
1	
Rated operating voltage (EF001435)	
690 V	
Rated permanent current I _u (EF001389)	
32 A	
Rated permanent current at AC-23, 400 V (EF011777)	
32 A	
Rated permanent current at AC-21, 400 V (EF009165)	
32 A	
Rated operation power at AC-3, 400 V (EF001364)	
11 kW	
Rated short-time withstand current I _{cw} (EF007050)	
0.65 kA	
Rated operation power at AC-23, 400 V (EF007027)	
15 kW	
Switching power at 400 V (EF009166)	
15 kW	
Conditioned rated short-circuit current I _q (EF001444)	
1 kA	
Number of poles (EF001391)	
2	
Number of auxiliary contacts as normally closed contact (EF001377)	
2	
Number of auxiliary contacts as normally open contact (EF001376)	
2	
Number of auxiliary contacts as change-over contact (EF003531)	
0	
Motor drive optional (EF007386)	
No	
Motor driv...	

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 172961 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.