

## INDUSTRIAL COMPONENT DATA

# 180A 690V AC TYPE T FUSE 180MMT EATON ELECTRIC cartridge fuse, ultra rapid, 180 A, AC 690 V, DC 350 V, BS88,...

Brand: EATON - MOELLER | Manufacturer Part Number: 180A 690V AC TYPE T FUSE



|                 |                          |
|-----------------|--------------------------|
| Manufacturer    | EATON - MOELLER          |
| MPN / Reference | 180A 690V AC TYPE T FUSE |
| Catalog number  | 180MMT                   |
| Category        | HRC fuse                 |
| Minimum order   | 1 Pcs                    |
| Document ID     | EO-2EE3AC3DC9            |
| Generated       | 2026-08-06               |

## Product Overview

cartridge fuse, ultra rapid, 180 A, AC 690 V, DC 350 V, BS88, 83 x 113 mm, aR, BS

180A 690V AC TYPE T FUSE

Eaton Bussmann series high speed British standard fuse, Double barrel, 180A, 690 VAC/350 VDC (IEC), 700 VAC (UL), Class aR, Breaking capacity 200 kA RMS Sym., 40 kA DC at 350 VDC (IEC)

Fuse, Fuse-link, high speed, 180 A, AC 690 V, DC 350 V, BS88, 83 x 113 mm, aR, BS, centre-bolted tags (dual barrel), DC common bus, DC drives, power converters/rectifiers and reduced voltage starters, BS88-4, IEC 60269-4, Breaking Capacity 200 kA, Optional accessories fuse-holder BH-3133

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                    |
|--------------|----------------------------------------------------|
| Catalog path | EATON - MOELLER > Bussmann Series High speed fuses |
|--------------|----------------------------------------------------|

## Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed british standard fuse Catalog Number 180MMT EAN 5027590036269

UPC 051712832090 Product Length/Depth 98 mm Product Height 40 mm Product Width 97 mm Product Weight 478 g

Compliances CE Marked

RoHS Compliant Certifications IEC Rated

UL Recognized

Designed and tested to BS88 part 4

IEC 60269-4

UL recognized Product specifications

Type Fuse Application Semiconductor, DC Common bus, DC drives, power converters/rectifiers Amperage Rating 180 A Breaking capacity 200 kA Fuse indicator None Insulated metal gripping lugs (IMGL) No Utilization category aR (accompanied semiconductor protection) Voltage type AC/DC Rated switching capacity 200 kA Rated voltage AC 690 V Rated voltage DC 350 V Center-to-center distance of connections 85 mm Mounting dimension M8 Current type AC/DC Class Class aR Clearing (I2T) 12000 Watt losses 42 W Fuse shape Center dual barrel bolted tags Pre arc (I2T) 1650 Color None Interrupt rating 200 kA RMS Sym (IEC/UL), 40 kA at 350 Vdc (IEC) Connection Blade end x blade end Construction size Other Mounting method Stud Packaging type Standard Voltage rating 690 V (IEC), 700 V (UL) Fuse type MMT Suitable for MC-700 Trip indicator kit (indicator + clips)

TI700 Fuse indicator

MAI Microswitch/adaptor

MBI Microswitch/adaptor Fuse system (according to IEC 60269) Other

ETIM for 180MMT Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Other

Fuse co...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 180A 690V AC TYPE T FUSE with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.