

INDUSTRIAL COMPONENT DATA

200A 690V AC TYPE T FUSE 200FEE 200FEE EATON ELECTRIC Fuse-link, high speed, 700 A, AC 690 V, DIN 1, 53 x 66..

Brand: EATON - MOELLER | Manufacturer Part Number: 200A 690V AC TYPE T FUSE



Manufacturer	EATON - MOELLER
MPN / Reference	200A 690V AC TYPE T FUSE
Catalog number	200FEE
Category	HRC fuse
Minimum order	5 Pcs
Document ID	EO-F5A732DB7E
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 700 A, AC 690 V, DIN 1, 53 x 66 x 138 mm, aR, DIN, IEC, type T indicator
fuse cartridge, ultra-fast, 200 A, AC 690 V, DC 500 V, BS88, 37 x 94 mm, aR, BS

200A 690V AC TYPE T FUSE - Fuse-link, high speed, 200 A, AC 690 V, DC 500 V, 200 kA, BS88, 37 x 94 mm, aR, BS
Fuse, Fuse-link, high speed, 200 A, AC 690 V, DC 500 V, BS88, 37 x 94 mm, aR, BS, offset bolted tags (dual barrel), DC
common bus, DC drives, power converters/rectifiers and reduced voltage starters, BS88-4, IEC 60269-4, Breaking Capacity
200 kA, Optional accessories fuse-holder BH-1132

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series High speed fuses

Additional Product Information

Fuse-link, high speed, 200 A, AC 690 V, DC 500 V, 200 kA, BS88, 37 x 94 mm, aR, BS Fuse, Fuse-link, high speed, 200 A,
AC 690 V, DC 500 V, BS88, 37 x 94 mm, aR, BS, offset bolted tags (dual barrel), DC common bus, DC drives, power
converters/rectifiers and reduced voltage starters, BS88-4, IEC 60269-4, Breaking Capacity 200 kA, Optional accessories
fuse-holder BH-1132 Delivery program

Product range Fuse Basic function Fuse-link Field of application high speed Rated current [I]_N 200 A Rated voltage AC 690 V
DC 500 V Construction size BS88 Size 37 x 94 mm Utilization category aR Breaking Capacity 200 kA Suitable for
size/applications DC common bus, DC drives, power converters/rectifiers and reduced voltage
starters Standard/Approval BSS Shape offset bolted tags (dual barrel) Standards/Regulations BS88-4

IEC 60269-4Optional accessoriesfuse-holder BH-1132Technical data ETIM 7.0
Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)Electric engineering, automation, process
control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (
[AFZ800015])Construction sizeOtherRated current200 ARated voltage690 VVoltage typeAC/DCRated switching
capacity200 kAUtilization categoryaR (accompanied semiconductor protection)Type of fuse status indicatorNoneInsulated
metal gripping lugs (IMGL)No
ETIM for 200FEE Circuit breakers and fuses (EC004556)
Feature Name
Feature Value
Fuse system according to IEC 60269 (EF017676)
Other
Fuse construction type accord...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 200A 690V AC TYPE T FUSE with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.