

INDUSTRIAL COMPONENT DATA

200A 690V THYRISTOR FUSE (1) 200CFM EATON ELECTRIC

Fuse-link, high speed, 50 A, AC 690 V, DC 500 V, BS88, 18..

Brand: EATON - MOELLER | Manufacturer Part Number: 200A 690V THYRISTOR FUSE (1)



Manufacturer	EATON - MOELLER
MPN / Reference	200A 690V THYRISTOR FUSE (1)
Catalog number	200CFM
Category	HRC fuse
Minimum order	1 Pcs
Document ID	EO-A430E935BA
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 50 A, AC 690 V, DC 500 V, BS88, 18 x 96 mm, aR, BS

200A 690V THYRISTOR FUSE (1)

200A 690V THYRISTOR FUSE (1) - Fuse-link, high speed, 200 A, AC 690 V, DC 450 V, 250 kA, BS88, 38 x 136 mm, aR, BS, 110 mm fixing centres

Fuse, Fuse-link, high speed, 200 A, AC 690 V, DC 450 V, BS88, 38 x 136 mm, aR, BS, offset bolted tags (slotted), 110 mm fixing centres, thyristor protection, BS88-4, IEC 60269-4, Breaking Capacity 250 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series High speed fuses

Additional Product Information

Fuse-link, high speed, 200 A, AC 690 V, DC 450 V, 250 kA, BS88, 38 x 136 mm, aR, BS, 110 mm fixing centres
Fuse-link, high speed, 200 A, AC 690 V, DC 450 V, BS88, 38 x 136 mm, aR, BS, offset bolted tags (slotted), 110 mm fixing centres, thyristor protection, BS88-4, IEC 60269-4, Breaking Capacity 250 kA
Delivery program

Product range FuseBasic function Fuse-linkField of application high speedRated current [I]_N 200 ARated voltage AC 690 V
DC 450 VConstruction size BS88Size 38 x 136 mmUtilization category aRDescription 110 mm fixing centresBreaking Capacity 250 kAusable for size/application thyristor protectionStandard/Approval BSShape offset bolted tags (slotted)Standards/Regulations BS88-4

IEC 60269-4Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse ()

[AFZ800015])Construction sizeOtherRated current200 ARated voltage690 VVoltage typeAC/DCRated switching capacity250 kAUtilization categoryaR (accompanied semiconductor protection)Type of fuse status indicatorNoneInsulated metal gripping lugs (IMGL)No
ETIM for 200CFM Circuit breakers and fuses (EC004556)
Feature Name
Feature Value
Fuse system according to IEC 60269 (EF017676)
Other
Fuse construction type according to IEC 60269 (EF015865)
Other
Type of current (EF000143)
AC/DC
Rated voltage AC (EF007682)
690 V
Rated voltage DC (EF012281)
450...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 200A 690V THYRISTOR FUSE (1) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.