

INDUSTRIAL COMPONENT DATA

200Amp 415Vac FEEDER PILLAR FUSE 200MJ30-8 EATON ELECTRIC cartridge fuse Utility, BT, 200 A, AC 415 V, BS88/..

Brand: EATON - MOELLER | Manufacturer Part Number: 200Amp 415Vac FEEDER PILLAR FUSE



Manufacturer	EATON - MOELLER
MPN / Reference	200Amp 415Vac FEEDER PILLAR FUSE
Catalog number	200MJ308
Category	HRC fuse
Minimum order	10 Pcs
Document ID	EO-0C9E852201
Generated	2026-08-06

Product Overview

cartridge fuse Utility, BT, 200 A, AC 415 V, BS88/J, 31 x 110 mm, gL/gG, BS

Fuse, Utility fuse-link, low voltage, 200 A, AC 415 V, BS88/J, 31 x 110 mm, gU, BS, dual bolted tags (slotted), 82 mm fixing centres, feeder pillars, BS88-2, IEC 60269-2, Breaking Capacity 80 kA, Optional accessories fuse-holder JW3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Busmann fuses
--------------	---------------------------------

Additional Product Information

Varistor suppressor, 415VAC, for DILE, screw connection Alternate Catalog No. XTMCXVSN EL-Nummer (Norway)

0004130399 Varistor suppressor circuit, Accessories: Suppressor circuit, Description: Varistor suppressor, Actuating voltage: Us 380 - 415 AC V, For use with: DILE... [Delivery program

Accessories Suppressor circuit Description Varistor suppressor Actuating voltage [Us] 380 - 415 AC V Contact sequence

For use with DILE... Instructions For AC operation contactors 50 - 60 Hz.

The suppressor is fitted as standard in DC operated contactor relays.

Note drop-out delay , Design verification as per IEC/EN 61439

Technical data for design verification Rated operational current for specified heat dissipation [In] 0 A Heat dissipation per pole, current-dependent [Pvid] 0 W Equipment heat dissipation, current-dependent [Pvid] 0 W Static heat dissipation, non-current-dependent [Pvs] 0 W Heat dissipation capacity [Pdiss] 0 W Operating ambient temperature min. -25 °C

Operating ambient temperature max. +50 °C IEC/EN 61439 design verification 10.2 Strength of materials and parts10.2.2

Corrosion resistance Meets the product standard's requirements. 10.2 Strength of materials and parts10.2.3.1 Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2 Strength of materials and parts10.2.3.2

Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2 Strength of materials and parts10.2.3.3 Verificatio...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 200Amp 415Vac FEEDER PILLAR FUSE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.