

INDUSTRIAL COMPONENT DATA

20HD36 EATON ELECTRIC Fuse-link, high speed, 10 A, AC 1200 V, DC 750 V, 22 x 138 mm, gL/gG, BS

Brand: EATON - MOELLER | Manufacturer Part Number: 20HD36



Manufacturer	EATON - MOELLER
MPN / Reference	20HD36
Catalog number	10000
Category	HRC fuse
Minimum order	10 Pcs
Document ID	EO-4E6A30DFDF
Generated	2026-08-06

Product Overview

20A 1200 VAC 750 VDC INDUSTRIAL FUSE

20HD36 - Fuse-link, high speed, 20 A, AC 1200 V, DC 750 V, 22 x 138 mm, gL/gG, BS

Fuse, Fuse-link, high speed, 20 A, AC 1200 V, DC 750 V, 22 x 138 mm, gL/gG, BS, offset bolted tags (slotted), traction, BS, Breaking Capacity 80 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series Low Voltage fuses and accessories

Additional Product Information

Fuse-link, high speed, 20 A, AC 1200 V, DC 750 V, 22 x 138 mm, gL/gG, BS
Fuse, Fuse-link, high speed, 20 A, AC 1200 V, DC 750 V, 22 x 138 mm, gL/gG, BS, offset bolted tags (slotted), traction, BS, Breaking Capacity 80 kA

General specificationsProduct nameEaton Bussmann series high speed traction fusePart

no.20HD36EAN5027590467896Product Length/Depth137 millimetreProduct height23 millimetreProduct width23

millimetreProduct weight94.5 gramComplianceRoHS CompliantCertificationsBSProduct TradenameNoneProduct

TypeHigh speed traction fuseProduct Sub TypeNoneElectrical dataAmperage Rating20 AVoltage rating1200 VProduct

specificationsApplicationtractionFuse indicatorNoneTechnical data ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)Electric engineering, automation, process control

engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) ()

[BAB264011])Fuse construction type according to IEC 60269OtherType of currentAC/DCRated voltage AC1,200 VRated

voltage DC750 VRated current20 AUtilization categorygL/gG (cable protection/equipment protection)Breaking capacity80

kAColour codeNoneType of fuse status indicatorNonePower loss at rated current5 WMounting holesM5Centre-to-centre

distance of connections122.4 mm

ETIM for 20HD36 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Other

Fuse construction type according to IEC 60269 (EF015865)

Other

Typ...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 20HD36 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.