

INDUSTRIAL COMPONENT DATA

20A 440V AC BS88 FUSE NS20 EATON ELECTRIC Fuse-link, low voltage, 710 A, AC 550 V, DC 250 V, BS88, BS, IEC

Brand: EATON - MOELLER | Manufacturer Part Number: 20A 440V AC BS88 FUSE



Manufacturer	EATON - MOELLER
MPN / Reference	20A 440V AC BS88 FUSE
Catalog number	NS20
Category	HRC fuse
Minimum order	20 Pcs
Document ID	EO-AC6DDE801D
Generated	2026-08-06

Product Overview

Fuse-link, low voltage, 710 A, AC 550 V, DC 250 V, BS88, BS, IEC

20A 440V AC BS88 FUSE

Fuse-link, low voltage, 20 A, AC 440 V, 80 kA, BS88/F1, 15 × 62 mm, gL/gG, BS

Fuse, Fuse-link, low voltage, 20 A, AC 440 V, BS88/F1, 15 x 62 mm, gL/gG, BS, offset bladed tags, general industrial applications, BS88-2, IEC 60269-2, Breaking Capacity 80 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series Low Voltage fuses and accessories

Additional Product Information

Fuse-link, low voltage, 20 A, AC 440 V, 80 kA, BS88/F1, 15 × 62 mm, gL/gG, BS
Fuse-link, low voltage, 20 A, AC 440 V, BS88/F1, 15 x 62 mm, gL/gG, BS, offset bladed tags, general industrial applications, BS88-2, IEC 60269-2, Breaking Capacity 80 kA
Delivery program

Product range Fuse
Basic function Fuse-link
Field of application low voltage
Rated current [I]_n 20 A
Rated voltage AC 440 V
Construction size BS88/F1
Size 15 × 62 mm
Utilization category gL/gG
Breaking Capacity 80 kA
Suitable for size/applications general industrial applications
Standard/Approval BS
Shape offset bladed tags
Standards/Regulations BS88-2 IEC 60269-2
Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse ()
[AFZ800015])
Construction size Other
Rated current 20 A
Rated voltage 440 V
Voltage type AC
Rated switching capacity 80 kA
Utilization category gL/gG (cable protection/equipment protection)
Type of fuse status indicator None
Insulated metal

gripping lugs (IMGL)No

ETIM for NS20 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Fuse system E

Fuse construction type according to IEC 60269 (EF015865)

F1

Type of current (EF000143)

AC

Rated voltage AC (EF007682)

440 V

Rated current (EF000227)

20 A

Utilization category according to IEC 60269 (EF002572)

gG (cable protection/equipment protectio...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 20A 440V AC BS88 FUSE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.