

INDUSTRIAL COMPONENT DATA

20A 690V AC TYPE T FUSE 20ET EATON ELECTRIC Fuse-link, high speed, 20 A, AC 690 V, DC 500 V, BS88, 19 x 77 m..

Brand: EATON - MOELLER | Manufacturer Part Number: 20A 690V AC TYPE T FUSE



Manufacturer	EATON - MOELLER
MPN / Reference	20A 690V AC TYPE T FUSE
Catalog number	20ET
Category	HRC fuse
Minimum order	10 Pcs
Document ID	EO-588B1B2F9E
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 20 A, AC 690 V, DC 500 V, BS88, 19 x 77 mm, aR, BS

20A 690V AC TYPE T FUSE

20A 690V AC TYPE T FUSE - Fuse-link, high speed, 20 A, AC 690 V, DC 500 V, 200 kA, BS88, 19 x 77 mm, aR, BS

Fuse, Fuse-link, high speed, 20 A, AC 690 V, DC 500 V, BS88, 19 x 77 mm, aR, BS, offset bolted tags, protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage starters, BS88-4, IEC 60269-4, Breaking Capacity 200 kA, Optional accessories fuse-holder BH-0111

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series High speed fuses

Additional Product Information

Fuse-link, high speed, 20 A, AC 690 V, DC 500 V, 200 kA, BS88, 19 x 77 mm, aR, BS Fuse, Fuse-link, high speed, 20 A, AC 690 V, DC 500 V, BS88, 19 x 77 mm, aR, BS, offset bolted tags, protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage starters, BS88-4, IEC 60269-4, Breaking Capacity 200 kA, Optional accessories fuse-holder BH-0111 Delivery program

Product range Fuse Basic function Fuse-link Field of application high speed Rated current [I]_n 20 A Rated voltage AC 690 V DC 500 V Construction size BS88 Size 19 x 77 mm Utilization category aR Breaking Capacity 200 kA Suitable for size/applications protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage starters Standard/Approval BSS Shape offset bolted tags Standards/Regulations BS88-4

IEC 60269-4 Optional accessories fuse-holder BH-0111 Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) Electric engineering, automation, process

control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (
[AFZ800015])Construction sizeOtherRated current20 ARated voltage690 VVoltage typeAC/DCRated switching capacity200
kAUtilization categoryOtherType of fuse status indicatorNoneInsulated metal gripping lugs (IMGL)No
ETIM for 20ET Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Other

Fuse construction type according to IEC 60269 (EF015865)

Other

Type of....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 20A 690V AC TYPE T FUSE with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.