

INDUSTRIAL COMPONENT DATA

20AMP 690V AC BS88 FUSE 20CT EATON ELECTRIC

Fuse-link, high speed, 50 A, AC 690 V, DC 500 V, BS88, 18 x 96 m..

Brand: EATON - MOELLER | Manufacturer Part Number: 20AMP 690V AC BS88 FUSE



Manufacturer	EATON - MOELLER
MPN / Reference	20AMP 690V AC BS88 FUSE
Catalog number	20CT
Category	HRC fuse
Minimum order	20 Pcs
Document ID	EO-7C2A8FA9A3
Generated	2026-08-06

Product Overview

Fuse-link, high speed, 50 A, AC 690 V, DC 500 V, BS88, 18 x 96 mm, aR, BS

20AMP 690V AC BS88 FUSE

Eaton Bussmann series high speed British standard fuse, 20A, 200 kAIC, None, Fuse, Blade end X blade end, Stud

Fuse, Fuse-link, high speed, 20 A, AC 690 V, DC 500 V, BS88, 9 x 75 mm, aR, BS, offset bolted tags, protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage starters, BS88-4, IEC 60269-4, Breaking Capacity 200 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series High speed fuses

Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed british standard fuse Catalog Number 20CT EAN 5027590467704 UPC 051712832304 Product Length/Depth 73 mm Product Height 9 mm Product Width 9 mm Product Weight 8.6 g Compliances CE Marked

RoHS Compliant Certifications IEC Rated

UL Recognized

Designed and tested to BS88 part 4

IEC 60269-4 Product specifications

Type Fuse Application Semiconductor, DC Common bus, DC drives, power converters/rectifiers Amperage Rating 20 A
Breaking capacity 90 kA Fuse indicator Non Indicating Insulated metal gripping lugs (IMGL) No Utilization category aR
(accompanied semiconductor protection) Voltage type AC/DC Rated switching capacity 200 kA Rated voltage AC 690 V
Rated voltage DC 500 V Center-to-center distance of connections 64.2 mm Mounting dimension Other Current type AC/DC
Class Class aR Clearing (I2T) 150 Watt losses 7 W Fuse shape Offset bolted tags Pre arc (I2T) 32 Color None Interrupt
rating 90 kA RMS Sym, 40 kA at 500 Vdc (IEC)
200 kA RMS Sym, 50 kA at 500 Vdc (UL) Connection Blade end x blade end Construction size Other Mounting method
Stud Packaging type Standard Voltage rating 690 V (IEC), 700 V (UL) Fuse type CT Suitable for T1700 Fuse indicator
MAI Microswitch/adaptor
MBI Microswitch/adaptor Fuse system (according to IEC 60269) Other
ETIM for 20CT Circuit breakers and fuses (EC004556)
Feature Name
Feature Value
Fuse system according to IEC 60269 (EF017676)
Other
Fuse construction type according to IEC 60269 (EF0...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 20AMP 690V AC BS88 FUSE with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.