

INDUSTRIAL COMPONENT DATA

20AMP 700V AC SEMI-COND FWP-20B EATON ELECTRIC cartridge fuse, ultrafast, 20 A, AC 700 V DC 700 V, 15 x 73 m..

Brand: EATON - MOELLER | Manufacturer Part Number: 20AMP 700V AC SEMI-COND



Manufacturer	EATON - MOELLER
MPN / Reference	20AMP 700V AC SEMI-COND
Catalog number	FWP-20B
Category	HRC fuse
Minimum order	10 Pcs
Document ID	EO-5ED3FD4E45
Generated	2026-08-06

Product Overview

cartridge fuse, ultrafast, 20 A, AC 700 V DC 700 V, 15 x 73 mm, aR, UL

20AMP 700V AC SEMI-COND

Eaton Bussmann series FWP high speed fuse, 700 Vac (UL), 690 Vac (IEC), 500 Vdc (2-100A), 500 Vac, 20A, 200 kAIC Vac, 50 kAIC at 700 Vdc, None, High speed fuse, Blade end X blade end, Stud

Fuse, Fuse-link, high speed, 20 A, AC 700 V, DC 700 V, 15 x 73 mm, aR, UL, centre-bolted tags, protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage starters, UL248, Breaking Capacity 200 kA, Optional accessories fuse-holder BH series

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series High speed fuses

Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed cylindrical fuse Catalog Number FWP-20B EAN 5027590500333 UPC 051712557818 Product Length/Depth 73 mm Product Height 15 mm Product Width 15 mm Product Weight 24.5 g

Compliances CE Marked

RoHS Compliant Certifications CSA Certified

UL Recognized Electrical data

Amperage Rating 20 A Voltage rating 700 Vac, 700 Vdc (UL) Voltage type AC/DC Interrupt rating 200 kAIC Vac

50 kAIC at 700 Vdc

200 kAIC at 300 Vdc

50 kAIC at 300 Vdc Class Class aR Pre arc (I2T) 26 Clearing (I2T) 180 at 700 V Watt losses 6 W Product specification
Application Semiconductor, DC Common bus, DC drives, Power converters/rectifiers Fuse indicator Non Indicating Fuse
size 22 x 58 mm

ETIM for FWP-20B Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Other

Fuse construction type according to IEC 60269 (EF015865)

Other

Type of current (EF000143)

AC/DC

Rated voltage AC (EF007682)

700 V

Rated voltage DC (EF012281)

700 V

Rated current (EF000227)

20 A

Utilization category according to IEC 60269 (EF002572)

aR (accompanied semiconductor protection)

Breaking capacity (EF005617)

200 kA

Colour code (EF000931)

None

Type of fuse status indicator (EF004473)

None

Power loss at rated current (EF012389)

6 W

Mounting holes (EF021553)

M6

Centre-to-centre distance of connections (EF021151)

63.35 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 20AMP 700V AC SEMI-COND with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.