

INDUSTRIAL COMPONENT DATA

20Amp FERULE OF LCT 20LCTF EATON ELECTRIC cartridge fuse, ultrafast, 20 A, AC 240 V, DC 150 V, BS88, 9 x 27 ..

Brand: EATON - MOELLER | Manufacturer Part Number: 20Amp FERULE OF LCT



Manufacturer	EATON - MOELLER
MPN / Reference	20Amp FERULE OF LCT
Catalog number	20LCTF
Category	HRC fuse
Minimum order	20 Pcs
Document ID	EO-0ED6DF279E
Generated	2026-08-06

Product Overview

cartridge fuse, ultrafast, 20 A, AC 240 V, DC 150 V, BS88, 9 x 27 mm, aR, BS

20Amp FERULE OF LCT

Fuse-link, high speed, 20 A, AC 240 V, DC 150 V, BS88, 9 x 27 mm, aR, BS

Fuse, Fuse-link, high speed, 20 A, AC 240 V, DC 150 V, BS88, 9 x 27 mm, aR, BS, cylindrical, Ferrule version of 20LCT, BS88-4, IEC 60269-4, Breaking Capacity 200 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series High speed fuses

Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed british standard fuse Catalog Number 20LCTF EAN 5027590467964

Product Length/Depth 52 mm Product Height 20 mm Product Width 84 mm Product Weight 5.25 g Compliances CE

Electrical data

Amperage Rating 20 A Voltage rating 240 V Rated voltage AC 240 V Rated voltage DC 150 V Interrupt rating 200 kA RMS

Sym, 50 kA DC at 150 Vdc Class Class aR Pre arc (I2T) 25 Clearing (I2T) 160 Watt losses 4 W Product specifications

Application Semiconductor, DC Common bus, DC drives, power converters/rectifiers Fuse indicator None

ETIM for 20LCTF Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Other

Fuse construction type according to IEC 60269 (EF015865)

Other

Type of current (EF000143)

AC/DC

Rated voltage AC (EF007682)

240 V

Rated voltage DC (EF012281)

150 V

Rated current (EF000227)

20 A

Utilization category according to IEC 60269 (EF002572)

aR (accompanied semiconductor protection)

Breaking capacity (EF005617)

200 kA

Colour code (EF000931)

None

Type of fuse status indicator (EF004473)

None

Power loss at rated current (EF012389)

4 W

Mounting holes (EF021553)

Other

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 20Amp FERULE OF LCT with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.