

INDUSTRIAL COMPONENT DATA

20H07-660 EATON ELECTRIC Fuse-link, low voltage, 20 A, AC 660 V, DC 250 V, BS88/A2, 22 x 82 mm, gL/gG, BS

Brand: EATON - MOELLER | Manufacturer Part Number: 20H07-660



Manufacturer	EATON - MOELLER
MPN / Reference	20H07-660
Catalog number	20H07660
Category	HRC fuse
Minimum order	20 Pcs
Document ID	EO-4EC37989B6
Generated	2026-08-06

Product Overview

20AMP 690V AC/ 460V DC INDUSTRIAL FUSE

Fuse-link, low voltage, 20 A, AC 690 V, DC 460 V, BS88/A2, 22 x 82 mm, gL/gG, BS

Fuse, Fuse-link, low voltage, 20 A, AC 660 V, DC 250 V, BS88/A2, 22 x 82 mm, gL/gG, BS, offset bolted tags, general industrial applications, BS88-2, IEC 60269-2, Breaking Capacity 80 kA, Ceramic body, Optional accessories fuse-holder CM32F

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series Low Voltage fuses and accessories

Additional Product Information

General specifications

Product Name Eaton Bussmann series low voltage british standard fuse Catalog Number 20H07-660 EAN 5027590467872

UPC 051712674379 Product Length/Depth 84.5 mm Product Height 21 mm Product Width 21 mm Product Weight 48.5 g

Compliances Contact Manufacturer Electrical data

Amperage Rating 20 A Voltage rating 690 V Voltage type AC/DC Breaking capacity 80 kA Class Class gG/gL Product specifications

Fuse type H07-660 Fitted with: Offset bolted tags Construction BS88/A2

ETIM for 20H07-660 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Fuse system E

Fuse construction type according to IEC 60269 (EF015865)

A2

Type of current (EF000143)

AC/DC

Rated voltage AC (EF007682)

690 V

Rated voltage DC (EF012281)

460 V

Rated current (EF000227)

20 A

Utilization category according to IEC 60269 (EF002572)

gG (cable protection/equipment protection)

Breaking capacity (EF005617)

80 kA

Colour code (EF000931)

None

Type of fuse status indicator (EF004473)

None

Power loss at rated current (EF012389)

2.7 W

Mounting holes (EF021553)

M5

Centre-to-centre distance of connections (EF021151)

71.5 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 20H07-660 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.