

INDUSTRIAL COMPONENT DATA

20M25 AMP 440V AC BS88 gM FUSE NIT20M25 EATON ELECTRIC Fuse-link, low voltage, 63A, AC 500 V, BS88, 21 x 114..

Brand: EATON - MOELLER | Manufacturer Part Number: 20M25 AMP 440V AC BS88 gM FUSE



Manufacturer	EATON - MOELLER
MPN / Reference	20M25 AMP 440V AC BS88 gM FUSE
Catalog number	NIT20M25
Category	HRC fuse
Minimum order	20 Pcs
Document ID	EO-9EDFBE9D83
Generated	2026-08-06

Product Overview

Fuse-link, low voltage, 63A, AC 500 V, BS88, 21 x 114 mm, gM, BS, 63M100

20M25 AMP 440V AC BS88 gM FUSE

20M25 AMP 440V AC BS88 gM FUSE - Fuse-link, low voltage, 20 A, AC 440 V, 80 kA, BS88/A1, 14 x 56 mm, gM, BS, motor-rated

Fuse, Fuse-link, low voltage, 20 A, AC 440 V, BS88/A1, 14 x 56 mm, gM, BS, offset bolted tags (slotted), general industrial applications, BS88-2, IEC 60269-2, Breaking Capacity 80 kA, Optional accessories fuse-holder CM32FC RS20

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Bussmann Series Low Voltage fuses and accessories
--------------	---

Additional Product Information

Fuse-link, low voltage, 20 A, AC 440 V, 80 kA, BS88/A1, 14 x 56 mm, gM, BS, motor-rated
Fuse, Fuse-link, low voltage, 20 A, AC 440 V, BS88/A1, 14 x 56 mm, gM, BS, offset bolted tags (slotted), general industrial applications, BS88-2, IEC 60269-2, Breaking Capacity 80 kA, Optional accessories fuse-holder CM32FC RS20
Delivery program

Product range
FuseBasic function
Fuse-linkField of application
low voltageRated current [I]
20 AMotor current rating [I]
20M25 ARated voltageAC 440 VConstruction sizeBS88/A1Size14 x 56 mmUtilization categorygMDescriptionmotor-ratedBreaking Capacity80 kAusable for size/applicationsgeneral industrial applicationsStandard/ApprovalBSShapeoffset bolted tags (slotted)Standards/RegulationsBS88-2

IEC 60269-2Optional accessoriesfuse-holder CM32FC and RS20Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse ( [AFZ800015]) Construction size Other Rated current 20 A Rated voltage 440 V Voltage type AC Rated switching capacity 80 kA Utilization category Other Type of fuse status indicator None Insulated metal gripping lugs (IMGL) No ETIM for NIT20M25 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Fuse system E

Fuse construction type according to IEC 60269 (EF015865)

A1

Type of current (EF000143)

AC

Rated voltage AC (EF00768...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 20M25 AMP 440V AC BS88 gM FUSE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.