

INDUSTRIAL COMPONENT DATA

20M32 AMP 440V AC BS88 gM FUSE NIT20M32 EATON ELECTRIC Fuse-link, low voltage, 63A, AC 500 V, BS88, 21 x 114..

Brand: EATON - MOELLER | Manufacturer Part Number: 20M32 AMP 440V AC BS88 gM FUSE



Manufacturer	EATON - MOELLER
MPN / Reference	20M32 AMP 440V AC BS88 gM FUSE
Catalog number	NIT20M32
Category	HRC fuse
Minimum order	20 Pcs
Document ID	EO-048B5C8E74
Generated	2026-08-06

Product Overview

Fuse-link, low voltage, 63A, AC 500 V, BS88, 21 x 114 mm, gM, BS, 63M100

20M32 AMP 440V AC BS88 gM FUSE

20M32 AMP 440V AC BS88 gM FUSE - Fuse-link, low voltage, 20 A, AC 440 V, 80 kA, BS88/A1, 14 x 56 mm, gM, BS, motor-rated

Fuse, Fuse-link, low voltage, 20 A, AC 440 V, BS88/A1, 14 x 56 mm, gM, BS, offset bolted tags (slotted), general industrial applications, BS88-2, IEC 60269-2, Breaking Capacity 80 kA, Optional accessories fuse-holder CM32FC RS20

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series Low Voltage fuses and accessories

Additional Product Information

Fuse-link, low voltage, 20 A, AC 440 V, 80 kA, BS88/A1, 14 x 56 mm, gM, BS, motor-rated
Fuse, Fuse-link, low voltage, 20 A, AC 440 V, BS88/A1, 14 x 56 mm, gM, BS, offset bolted tags (slotted), general industrial applications, BS88-2, IEC 60269-2, Breaking Capacity 80 kA, Optional accessories fuse-holder CM32FC RS20
Delivery program

Product range Fuse
Basic function Fuse-link
Field of application low voltage
Rated current [I]
20 A
Motor current rating [I]
20M32 A
Rated voltage AC 440 V
Construction size BS88/A1
Size 14 x 56 mm
Utilization category gM
Description motor-rated
Breaking Capacity 80 kA
Usable for size/applications general industrial applications
Standard/Approval BS
Shape offset bolted tags (slotted)
Standards/Regulations BS88-2

IEC 60269-2
Optional accessories fuse-holder CM32FC and RS20
Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse ( [AFZ800015]) Construction size Other Rated current 20 A Rated voltage 440 V Voltage type AC Rated switching capacity 80 kA Utilization category Other Type of fuse status indicator None Insulated metal gripping lugs (IMGL) No ETIM for NIT20M32 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Fuse system E

Fuse construction type according to IEC 60269 (EF015865)

A1

Type of current (EF000143)

AC

Rated voltage AC (EF00768...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 20M32 AMP 440V AC BS88 gM FUSE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.