

INDUSTRIAL COMPONENT DATA

225A 690V AC TYPE T FUSE (1) 225MMT EATON ELECTRIC cartridge fuse, ultra rapid, 225 A, AC 690 V, DC 350 V, B..

Brand: EATON - MOELLER | Manufacturer Part Number: 225A 690V AC TYPE T FUSE (1)



Manufacturer	EATON - MOELLER
MPN / Reference	225A 690V AC TYPE T FUSE (1)
Catalog number	225MMT
Category	HRC fuse
Minimum order	1 Pcs
Document ID	EO-DA16FC11E6
Generated	2026-08-06

Product Overview

cartridge fuse, ultra rapid, 225 A, AC 690 V, DC 350 V, BS88, 83 x 113 mm, aR, BS

225A 690V AC TYPE T FUSE (1)

Eaton Busmann series high speed British standard fuse, Double barrel, 225A, 690 VAC/350 VDC (IEC), 700 VAC (UL), Class aR, Breaking capacity 200 kA RMS Sym., 40 kA DC at 350 VDC (IEC)

Fuse, Fuse-link, high speed, 225 A, AC 690 V, DC 350 V, BS88, 83 x 113 mm, aR, BS, centre-bolted tags (dual barrel), DC common bus, DC drives, power converters/rectifiers and reduced voltage starters, BS88-4, IEC 60269-4, Breaking Capacity 200 kA, Optional accessories fuse-holder BH-3133

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Busmann Series High speed fuses

Additional Product Information

General specifications

Product Name Eaton Busmann series high speed british standard fuse Catalog Number 225MMT EAN 5027590037518

UPC 051712832571 Product Length/Depth 98 mm Product Height 40 mm Product Width 97 mm Product Weight 464 g

Compliances CE Marked

RoHS Compliant Certifications IEC Rated

UL Recognized

Designed and tested to BS88 part 4

IEC 60269-4

UL recognized Electrical data

Amperage Rating 225 A Voltage rating 690 V (IEC), 700 V (UL) Rated voltage AC 690 V Rated voltage DC 350 V Interrupt rating 200 kA RMS Sym (IEC/UL), 40 kA at 350 Vdc (IEC) Class Class aR Pre arc (I2T) 3700 Clearing (I2T) 26000 Watt losses 42 W Product specifications

Application Semiconductor, DC Common bus, DC drives, power converters/rectifiers Fuse indicator None Compatible Trip indicator/Microswitch

Suitable for MC-700 Trip indicator kit (indicator + clips)

TI700 Fuse indicator

MAI Microswitch/adaptor

MBI Microswitch/adaptor

ETIM for 225MMT Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Other

Fuse construction type according to IEC 60269 (EF015865)

Other

Type of current (EF000143)

AC/DC

Rated voltage AC (EF007682)

690 V

Rated voltage DC (EF012281)

350 V

Rated current (EF000227)

225 A

Utilization category according to IEC 60269 (EF002572)

aR (accompanied semiconductor protection)

Breaking capacity (EF005617)

200 kA

Colour code (EF000931)

None

Type of fuse status indicator (EF004473)

None

Power loss at rated current (EF012389)

42...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 225A 690V AC TYPE T FUSE (1) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.