


INDUSTRIAL COMPONENT DATA

22DDILE-C 230264 XTMCXFCLC22 EATON ELECTRIC

Auxiliary contact, 1N/O+1N/O early+1N/C+1N/C late, surface mount..

Brand: EATON - MOELLER | Manufacturer Part Number: 22DDILE-C



Manufacturer	EATON - MOELLER
MPN / Reference	22DDILE-C
Catalog number	XTMCXFCLC22
Category	Auxiliary contact block
Minimum order	1 Pcs
Document ID	EO-7ED731A06E
Generated	2026-08-06

Product Overview

Auxiliary contact, 1N/O+1N/O early+1N/C+1N/C late, surface mounting, spring clamp connection

Auxiliary contact block; 1 NO + 1 NOA + 1 NC + 1 NCR; front Mounting; pressure Connection; To TELL her...

Auxiliary contact module, 4 pole, 1 N/O, 1 N/OE, 1 NC, 1 NCL, Front fixing, Spring-loaded terminals, DILE(E)M...-C, DILER...-C

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Contactors up to 170A
--------------	---

Additional Product Information

Auxiliary contact module, 4 pole, 1 N/O, 1 N/OE, 1 NC, 1 NCL, Front fixing, Spring-loaded terminals, DILE(E)M...-C, DILER...-CAuxiliary contact module, Function: for standard applications, 4 pole, Connection technique: Spring-loaded terminals, Rated operational current AC-15 220 V 230 V 240 V: Ie= 4 A, Rated operational current AC-15 380 V 400 V 415 V: Ie= 2 A, Rated operational current AC-15 380 V 400 V 500 V: Ie= 1.5 A, Contacts N/O = Normally open: 1 N/O, Contacts N/OE: NO early-make: 1 N/OE, Contacts N/C = Normally closed: 1 NC, Contacts NCL=NC late-break: 1 NCL, Mounting type: Front fixing, For use with: DILE(E)M-10-C(-G)(...), DILE(E)M-01-C(-G)(...), DILER40(-G)-C, DILER31(-G)-C, DILER22-C , Instructions: Auxiliary contacts used as mirror contacts according to IEC/EN 60947-4-1 Appendix F (not N/C late open), Code number and version of combination Distinctive number: 62, 53, 44

General specificationsProduct nameEaton Moeller® series DILE Accessory Auxiliary contact modulePart no.22DDILE-CEAN4015082302641Product Length/Depth39 millimetreProduct height37 millimetreProduct width45

millimetreProduct weight0.042 kilogramCertificationsUL File No.: E29184

CSA

VDE 0660

CE

UL 508

CSA-C22.2 No. 14-05

CSA File No.: 012528

CSA Class No.: 3211-03

UL Category Control No.: NKCR

UL

IEC/EN 60947

IEC/EN 60947-4-1Product TradenameDILEProduct TypeAccessoryProduct Sub TypeAuxiliary contact moduleCatalog

NotesAuxiliary contacts used as mirror contacts (according to IEC/EN 60947-4-1 Appendix F (not N...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 22DDILE-C with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.