

INDUSTRIAL COMPONENT DATA

24KV 20AMP 2" FULL RANGE FUSE 24FDIHA20 EATON

ELECTRIC Voltmeter selector switches, Contacts: 4, 20 A, 3 x p..

Brand: EATON - MOELLER | Manufacturer Part Number: 24KV 20AMP 2" FULL RANGE FUSE



Manufacturer	EATON - MOELLER
MPN / Reference	24KV 20AMP 2" FULL RANGE FUSE
Catalog number	24FDIHA20
Category	Medium-/high voltage fuse
Minimum order	3 Pcs
Document ID	EO-816B3389E3
Generated	2026-08-06

Product Overview

Voltmeter selector switches, Contacts: 4, 20 A, 3 x phase-N, front plate: 0-L1/N L2/N L3/N, 90 °, maintained, flush mounting
24KV 20AMP 2" FULL RANGE FUSE

24KV 20AMP 2" FULL RANGE FUSE - Fuse-link, medium voltage, 20 A, AC 24 kV, 35.5 kA, 2", 51 x 565 mm, full-range, BS, with striker

Fuse, Fuse-link, medium voltage, 20 A, AC 22 kV, 51 x 565 mm, full-range, BS, with striker, cylindrical, Protection of transformers, BS2692-1, Breaking Capacity 35.5 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Busmann Series Medium Voltage fuses and accessories

Additional Product Information

General specifications

Product Name Eaton Busmann series medium voltage BS air fuse Catalog Number 24FDIHA20 EAN 5027590468916

Product Length/Depth 590 mm Product Height 50.8 mm Product Width 50.8 mm Product Weight 2588.333 g Certifications BS 2692-1 Electrical data

Amperage Rating 20 A Voltage rating 24 kV Voltage type AC Breaking capacity 35.5 kA Performance Cat According To IEC 60282-1 Full-range Rated frequency - min 50 Hz Class Class full-range Pre arc (I2T) 1.3 x 103 Resistance 88.2 ohms

Product specification

Construction size 51 x 565 mm Standard British Standard Standard British Standard Mounting method Clip-in Compatible

fuse clip

Used with A3354710 Fuse clip

ETIM for 24FDIHA20 Circuit breakers and fuses (EC003507)

Feature Name

Feature Value

Rated current (EF000227)

20 A

Rated voltage (EF000228)

24 kV

Voltage type (EF000187)

AC

Rated frequency (EF001663)

50 Hz

Breaking capacity (EF005617)

35.5 kA

Utilization category according to IEC 60269 (EF002572)

Other

Application (EF000041)

Primary side transformer protection

Length (EF001438)

590 mm

Diameter (EF000551)

51 mm

Performance category according to IEC 60282-1 (EF012539)

Full range

With striker (EF008175)

Yes

Standard (EF009322)

British Standard

Release characteristic (EF000889)

Other

Installation technique (EF001474)

Air

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 24KV 20AMP 2" FULL RANGE FUSE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.