

INDUSTRIAL COMPONENT DATA

24KV 31.5AMP 2.5" OIL FUSE 24OEGMA31.5 24OEGMA31-5 EATON ELECTRIC Fuse, Air fuse-link, medium voltage, 10 A,..

Brand: EATON - MOELLER | Manufacturer Part Number: 24KV 31.5AMP 2.5" OIL FUSE



Manufacturer	EATON - MOELLER
MPN / Reference	24KV 31.5AMP 2.5" OIL FUSE
Catalog number	24OEGMA31-5
Category	Medium-/high voltage fuse
Minimum order	3 Pcs
Document ID	EO-B254355063
Generated	2026-08-06

Product Overview

Fuse, Air fuse-link, medium voltage, 10 A, AC 12 kV, 51 x 359 mm, back-up, BS, with striker, style 36 tags

24KV 31.5AMP 2.5" OIL FUSE

24KV 31.5AMP 2.5" OIL FUSE - Oil fuse-link, medium voltage, 31.5 A, AC 24 kV, 25 kA, BS2692 F02, 359 x 63.5 mm, back-up, BS, IEC, ESI, with striker, oil-tight

Fuse, Oil fuse-link, medium voltage, 31.5 A, AC 24 kV, BS2692 F02, 359 x 63.5 mm, back-up, BS, IEC, ESI, with striker, cylindrical, oil-tight, protection of primary side transformer, and oil-filled fuse switch combination unit, BS2692-1, IEC 60282-1, ESI 12-8, Breaking Capacity 25 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Bussmann Series Medium Voltage fuses and accessories

Additional Product Information

Oil fuse-link, medium voltage, 31.5 A, AC 24 kV, 25 kA, BS2692 F02, 359 x 63.5 mm, back-up, BS, IEC, ESI, with striker, oil-tight
Fuse, Oil fuse-link, medium voltage, 31.5 A, AC 24 kV, BS2692 F02, 359 x 63.5 mm, back-up, BS, IEC, ESI, with striker, cylindrical, oil-tight, protection of primary side transformer, and oil-filled fuse switch combination unit, BS2692-1, IEC 60282-1, ESI 12-8, Breaking Capacity 25 kA
Delivery program

Product range Fuse
Basic function Oil fuse-link
Field of application medium voltage
Rated current [I]_N 31.5 A
Rated voltage AC 24 kV
Construction size BS2692 F02
Size 359 x 63.5 mm
Utilization category back-up
Status indicator with striker
Description oil-tight
Breaking Capacity 25 kA
Usable for size/applications protection of primary side transformer, and oil-filled fuse switch combination unit
Standard/Approval BS IEC

ESIShapecylindricalStandards/RegulationsBS2692-1

IEC 60282-1

ESI 12-8Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Medium-/high voltage fuse (EC003507)Rated current31.5 ARated voltage24 kVVoltage typeACRated frequency50 - 50 HzBreaking capacity25 kAUtilization categoryOtherApplicationPrimary side transformer protectionLength359 mmDiameter63.5 mmPerformance category according to IEC 60282-1Back-upWith strikerYesStandardBritish StandardRelease characteristicOtherInstallation techniqueOil

ETIM for 24OEGMA31.5 Circuit breakers and fuses (EC003507)

Feature Name

Feature Value

Rated current (EF000227)

31.5 A

Rated voltage (EF000228)

24 kV

Voltage type....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 24KV 31.5AMP 2.5" OIL FUSE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.