

## INDUSTRIAL COMPONENT DATA

# 24KV 6.3AMP 2" FULL RANGE FUSE 24FDIHA6.3 XTPR6P3BC1NLSA11 EATON ELECTRIC cartridge fuse, MT, 6.3 A, AC 22 k..

Brand: EATON - MOELLER | Manufacturer Part Number: 24KV 6.3AMP 2" FULL RANGE FUSE



|                 |                                |
|-----------------|--------------------------------|
| Manufacturer    | EATON - MOELLER                |
| MPN / Reference | 24KV 6.3AMP 2" FULL RANGE FUSE |
| Catalog number  | XTPR6P3BC1NLSA11               |
| Category        | Medium-/high voltage fuse      |
| Minimum order   | 3 Pcs                          |
| Document ID     | EO-7748321659                  |
| Generated       | 2026-08-06                     |

## Product Overview

cartridge fuse, MT, 6.3 A, AC 22 kV, 51 x 565 mm, full-range, BS, with striker

24KV 6.3AMP 2" FULL RANGE FUSE

24KV 6.3AMP 2" FULL RANGE FUSE - Fuse-link, medium voltage, 6.3 A, AC 24 kV, 35.5 kA, 2", 51 x 565 mm, full-range, BS, with striker

Fuse, Fuse-link, medium voltage, 6.3 A, AC 22 kV, 51 x 565 mm, full-range, BS, with striker, cylindrical, Protection of transformers, BS2692-1, Breaking Capacity 35.5 kA

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path

EATON - MOELLER &gt; Busmann Series Medium Voltage fuses and accessories

## Additional Product Information

Fuse-link, medium voltage, 6.3 A, AC 24 kV, 35.5 kA, 2", 51 x 565 mm, full-range, BS, with striker  
Fuse, Fuse-link, medium voltage, 6.3 A, AC 24 kV, 51 x 565 mm, full-range, BS, with striker, cylindrical, Protection of transformers, BS2692-1, Breaking Capacity 35.5 kA  
Delivery program

Product range Fuse  
Basic function Fuse-link  
Field of application medium voltage  
Rated current [I]  
6.3 A  
Rated voltage AC 24 kV  
Construction size 2"  
Size 51 x 565 mm  
Utilization category full-range  
Status indicator with striker  
Breaking Capacity 35.5 kA  
Usable for size/applications Protection of

transformers  
Standard/Approval BS  
Shape cylindrical  
Standards/Regulations BS2692-1  
Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Medium-/high voltage fuse (EC003507)  
Rated current 6.3 A  
Rated voltage 24

kV Voltage type AC Rated frequency 50 - 50 Hz Breaking capacity 35.5 kA Utilization category Other Application Primary side transformer protection Length 565 mm Diameter 51 mm Performance category according to IEC 60282-1 Full-range With striker Yes Standard British Standard Release characteristic Other Installation technique Air ETIM for 24FDIHA6.3 Circuit breakers and fuses (EC003507)

Feature Name

Feature Value

Rated current (EF000227)

6.3 A

Rated voltage (EF000228)

24 kV

Voltage type (EF000187)

AC

Rated frequency (EF001663)

50 Hz

Breaking capacity (EF005617)

35.5 kA

Utilization category according to IEC 60269 (EF002572)

Other

Application (EF000041)

Primary side transformer protection

Length (EF001438)

565 mm

Diameter (EF000551)

51 mm

Perform...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 24KV 6.3AMP 2" FULL RANGE FUSE with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.