

INDUSTRIAL COMPONENT DATA

24TDMEJ25 EATON ELECTRIC Fuse-link, medium voltage, 25 A, AC 24 kV, 2", 51 x 442 mm, back-up, DIN, with stri..

Brand: EATON - MOELLER | Manufacturer Part Number: 24TDMEJ25



Manufacturer	EATON - MOELLER
MPN / Reference	24TDMEJ25
Catalog number	10000
Category	Medium-/high voltage fuse
Minimum order	1 Pcs
Document ID	EO-C8BC16F710
Generated	2026-08-06

Product Overview

24KV 25Amp 2" DIN Resin Seal Fuse

Fuse-link, medium voltage, 25 A, AC 24 kV, 2", 51 x 442 mm, back-up, DIN, with striker

Fuse, Fuse-link, medium voltage, 25 A, AC 24 kV, 2z, 51 x 442 mm, Back-up, DIN, with striker, transformer protection, indoor or outdoor use, DIN 43625, VDE 0670 Part 4, VDE 0670 Part 402, IEC 60282-1, Breaking Capacity 50 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Bussmann Series Medium Voltage fuses and accessories
--------------	--

Additional Product Information

General specifications

Product Name Eaton Bussmann series medium voltage DIN fuse Catalog Number 24TDMEJ25 EAN 5027590469296 UPC 051712186322 Product Length/Depth 442 mm Product Height 54 mm Product Width 51 mm Product Weight 2248 g

Compliances DIN 43625

VDE 0670-4

IEC 60282-1 Certifications IEC Rated Electrical data

Amperage Rating 25 A Voltage rating 24 kV Voltage type AC Breaking capacity 50 kA Performance Cat According To IEC 60282-1 Back-up Rated frequency - min 50 Hz Class Class back-up Resistance 62.4 Ohms Watt losses 49 W Product specifications

Fuse indicator With Striker Construction size 51 x 442 mm Standard DIN Standard DIN Mounting method Clip-in

Compatible fuse clip

Used with 270303 Fuse clip

A3354710 Fuse clip

ETIM for 24TDMEJ25 Circuit breakers and fuses (EC003507)

Feature Name

Feature Value

Rated current (EF000227)

25 A

Rated voltage (EF000228)

24 kV

Voltage type (EF000187)

AC

Rated frequency (EF001663)

50 Hz

Breaking capacity (EF005617)

50 kA

Utilization category according to IEC 60269 (EF002572)

Other

Application (EF000041)

Primary side transformer protection

Length (EF001438)

442 mm

Diameter (EF000551)

51 mm

Performance category according to IEC 60282-1 (EF012539)

Back-up

With striker (EF008175)

Yes

Standard (EF009322)

DIN

Release characteristic (EF000889)

Other

Installation technique (EF001474)

Air

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 24TDMEJ25 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.