

INDUSTRIAL COMPONENT DATA

250A 690V TYPE T FUSE (1) 250CFM EATON ELECTRIC cartridge fuse, ultra rapid, 250 A, AC 690 V, DC 450 V -, BS..

Brand: EATON - MOELLER | Manufacturer Part Number: 250A 690V TYPE T FUSE (1)



Manufacturer	EATON - MOELLER
MPN / Reference	250A 690V TYPE T FUSE (1)
Catalog number	250CFM
Category	HRC fuse
Minimum order	1 Pcs
Document ID	EO-DE171DF7C0
Generated	2026-08-06

Product Overview

cartridge fuse, ultra rapid, 250 A, AC 690 V, DC 450 V -, BS88, 38 x 136 mm, aR, BS

250A 690V TYPE T FUSE (1)

Fuse-link, high speed, 250 A, AC 690 V, DC 450 V, BS88, 38 x 136 mm, aR, BS

Fuse, Fuse-link, high speed, 250 A, AC 690 V, DC 450 V, BS88, 38 x 136 mm, aR, BS, offset bolted tags (slotted), 110 mm fixing centres, thyristor protection, BS88-4, IEC 60269-4, Breaking Capacity 250 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Busmann Series High speed fuses

Additional Product Information

General specifications

Product Name Eaton Busmann series high speed british standard fuse Catalog Number 250CFM EAN 5027590039215

Product Length/Depth 42 mm Product Height 42 mm Product Width 150 mm Product Weight 228 g Compliances CE

Electrical data

Amperage Rating 250 A Voltage rating 690 V Rated voltage AC 690 V Rated voltage DC 450 V Class Class aR Pre arc

(I2T) 5200 Clearing (I2T) 20500 Watt losses 48 W Product specifications

Application Semiconductor, DC Common bus, DC drives, power converters/rectifiers Fuse indicator None

ETIM for 250CFM Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Other

Fuse construction type according to IEC 60269 (EF015865)

Other

Type of current (EF000143)

AC/DC

Rated voltage AC (EF007682)

690 V

Rated voltage DC (EF012281)

450 V

Rated current (EF000227)

250 A

Utilization category according to IEC 60269 (EF002572)

aR (accompanied semiconductor protection)

Breaking capacity (EF005617)

200 kA

Colour code (EF000931)

None

Type of fuse status indicator (EF004473)

None

Power loss at rated current (EF012389)

48 W

Mounting holes (EF021553)

M10

Centre-to-centre distance of connections (EF021151)

110 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 250A 690V TYPE T FUSE (1) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.