

## INDUSTRIAL COMPONENT DATA

# 250A TYPE T FUSE (1) 250CMT EATON ELECTRIC cartridge fuse, ultra rapid, 250 A, AC 690v, BS88, 41 x 113 mm, a..

Brand: EATON - MOELLER | Manufacturer Part Number: 250A TYPE T FUSE (1)



|                 |                      |
|-----------------|----------------------|
| Manufacturer    | EATON - MOELLER      |
| MPN / Reference | 250A TYPE T FUSE (1) |
| Catalog number  | 250CMT               |
| Category        | HRC fuse             |
| Minimum order   | 1 Pcs                |
| Document ID     | EO-92EE0365C8        |
| Generated       | 2026-08-06           |

## Product Overview

cartridge fuse, ultra rapid, 250 A, AC 690v, BS88, 41 x 113 mm, aR, BS

250A TYPE T FUSE (1)

Fuse-link, high speed, 250 A, AC 690 V, 200 kA, BS88, 41 x 113 mm, aR, BS, 110 mm fixing centres

Fuse, Fuse-link, high speed, 250 A, AC 690 V, BS88, 41 x 113 mm, aR, BS, offset bolted tags (slotted), 110 mm fixing centres, DC common bus, DC drives, power converters/rectifiers and reduced voltage starters, BS88-4, IEC 60269-4, Breaking Capacity 200 kA, Optional accessories fuse-holder BH-1133

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                    |
|--------------|----------------------------------------------------|
| Catalog path | EATON - MOELLER > Bussmann Series High speed fuses |
|--------------|----------------------------------------------------|

## Additional Product Information

Fuse-link, high speed, 250 A, AC 690 V, 200 kA, BS88, 41 x 113 mm, aR, BS, 110 mm fixing centres  
Fuse, Fuse-link, high speed, 250 A, AC 690 V, BS88, 41 x 113 mm, aR, BS, offset bolted tags (slotted), 110 mm fixing centres, DC common bus, DC drives, power converters/rectifiers and reduced voltage starters, BS88-4, IEC 60269-4, Breaking Capacity 200 kA, Optional accessories fuse-holder BH-1133  
Delivery program

Product range Fuse Basic function Fuse-link Field of application high speed Rated current [I]<sub>n</sub> 250 A Rated voltage AC 690

V Construction size BS88 Size 41 x 113 mm Utilization category aR Description 110 mm fixing centres Breaking Capacity 200

kA Usable for size/applications DC common bus, DC drives, power converters/rectifiers and reduced voltage

starters Standard/Approval BSS Shape offset bolted tags (slotted) Standards/Regulations BS88-4

IEC 60269-4 Optional accessories fuse-holder BH-1133 Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) Electric engineering, automation, process

control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse ([email protected]  
[AFZ800015])Construction sizeOtherRated current250 ARated voltage690 VVoltage typeACRated switching capacity200  
kAUtilization categoryaR (accompanied semiconductor protection)Type of fuse status indicatorNoneInsulated metal gripping  
lugs (IMGL)No  
ETIM for 250CMT Circuit breakers and fuses (EC004556)  
Feature Name  
Feature Value  
Fuse system according to IEC 60269 (EF01...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 250A TYPE T FUSE (1) with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use  
[electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd  
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification  
requirements against the manufacturer documentation before purchase or installation.