

INDUSTRIAL COMPONENT DATA

NH FUSE 250A 400V GG/GL SIZE 1 250NHG1B-400 EATON

ELECTRIC Fuse-link, LV, 200 A, AC 400 V, NH1, gL/gG, IEC, ..

Brand: EATON - MOELLER | Manufacturer Part Number: NH FUSE 250A 400V GG/GL SIZE 1



Manufacturer	EATON - MOELLER
MPN / Reference	NH FUSE 250A 400V GG/GL SIZE 1
Catalog number	250NHG1B-400
Category	Low Voltage HRC fuse
Minimum order	3 Pcs
Document ID	EO-D1F896B000
Generated	2026-08-06

Product Overview

Fuse-link, LV, 200 A, AC 400 V, NH1, gL/gG, IEC, dual indicator, live gripping lugs

250A, AC 400V, NH1, Fuse with live lugs

NH FUSE 250A 400V GG/GL SIZE 1 - Fuse-link, low voltage, 250 A, AC 400 V, 120 kA, NH1, gL/gG, IEC, dual indicator, live gripping lugs

Fuse, fuse-link, low voltage, 250 A, AC 400 V, NH1, gL/gG, IEC, dual (combination) indicator system, square-body with knife blade contacts, live gripping lugs, IEC 60269-2 fuse system A, DIN 43620, VDE 0636-2. Breaking capacity 120 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series Low Voltage fuses and accessories

Additional Product Information

Fuse-link, low voltage, 250 A, AC 400 V, 120 kA, NH1, gL/gG, IEC, dual indicator, live gripping lugs
Fuse, fuse-link, low voltage, 250 A, AC 400 V, NH1, gL/gG, IEC, dual (combination) indicator system, square-body with knife blade contacts, live gripping lugs, IEC 60269-2 fuse system A, DIN 43620, VDE 0636-2. Breaking capacity 120 kA
Delivery program
Product range
FuseBasic function
Fuse-linkField of application
low voltageRated current [I]
250 ARated voltageAC 400 V
Construction sizeNH1Utilization categorygL/gGStatus indicator
dual indicatorDescriptionlive gripping lugs
Breaking Capacity120 kA
Usable for size/applicationsindustrial
Standard/ApprovalIECShapesquare body with knife blade contacts
Standards/RegulationsIEC 60269-2 fuse system A
DIN 43620

VDE 0636-2Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)Electric engineering, automation, process

control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (
[AFZ800015])Construction sizeNH1Rated current250 ARated voltage400 VVoltage typeACRated switching capacity120
kAUtilization categorygL/gG (cable protection/equipment protection)Type of fuse status indicatorCombination fuse status
indicatorInsulated metal gripping lugs (IMGL)No
ETIM for 250NHG1B-400 Circuit breakers and fuses (EC000055)
Feature Name
Feature Value
Fuse construction type according to IEC 60269 (EF015865)
NH1
Voltage type (EF000187)
AC
Rated current (EF000227)
250 A
R...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NH FUSE 250A 400V GG/GL SIZE 1 with the required quantity to info@electricaonline.com or
use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.