

INDUSTRIAL COMPONENT DATA

250NHM2B-690 EATON ELECTRIC cartridge fuse, BT 250 a, AC 690 V, NH2, a.m., IEC, indicator double, metal term..

Brand: EATON - MOELLER | Manufacturer Part Number: 250NHM2B-690



Manufacturer	EATON - MOELLER
MPN / Reference	250NHM2B-690
Catalog number	250NHM2B690
Category	Low Voltage HRC fuse
Minimum order	3 Pcs
Document ID	EO-5039470C59
Generated	2026-08-06

Product Overview

NH FUSE 250A 690V aM SIZE 2 DUAL IND

Fuse-link, LV, 250 A, AC 690 V, NH2, aM, IEC, dual indicator, live gripping lugs

Fuse, fuse-link, low voltage, 250 A, AC 690 V, NH2, aM, IEC, dual (combination) indicator system, square-body with knife blade contacts, live gripping lugs, IEC 60269-2 fuse system A, DIN 43620, VDE 0636-2. Breaking capacity 120 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series Low Voltage fuses and accessories

Additional Product Information

General specifications

Product Name Eaton Bussmann series low voltage NH Fuse Catalog Number 250NHM2B-690 EAN 5027590469838 UPC 051712386340 Product Length/Depth 150 mm Product Height 71 mm Product Width 54 mm Product Weight 659 g

Compliances CE Marked

RoHS Compliant Certifications IEC 60269-1

IEC 60269-2

DIN 43620 Electrical data

Amperage Rating 250 A Voltage rating 690 V Voltage type AC Breaking capacity 120 kA Class Class aM Frequency rating - min 45 Hz Frequency rating - max 62 Hz Product specification

Fuse size NH2 Insulated metal gripping lugs (IMGL) No Accessories

Suitable for SD2-D Single pole NH Fuse base

TD2-D Tripe pole NH Fuse base

Microswitch 170H0235
Microswitch 170H0236
EBH Size 00 to 4 Horizontal fuse switch-disconnectors
ETIM for 250NHM2B-690 Circuit breakers and fuses (EC000055)
Feature Name
Feature Value
Fuse construction type according to IEC 60269 (EF015865)
NH2
Voltage type (EF000187)
AC
Rated current (EF000227)
250 A
Rated voltage AC (EF007682)
690 V
Rated switching capacity AC (EF017698)
120 kA
Utilization category according to IEC 60269 (EF002572)
aM (switchgear protection)
Type of fuse status indicator (EF004473)
Combination fuse status indicator
Insulated metal gripping lugs (IMGL) (EF012538)
No
Power loss at rated current (EF012389)
17 W

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 250NHM2B-690 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.