

INDUSTRIAL COMPONENT DATA

FWP-25A14F EATON ELECTRIC Fuse-link, High speed, 1 A, AC 600 V, 14.3 x 73.0 mm, UR

Brand: EATON - MOELLER | Manufacturer Part Number: FWP-25A14F



Manufacturer	EATON - MOELLER
MPN / Reference	FWP-25A14F
Catalog number	10000
Category	Cylindrical fuse
Minimum order	10 Pcs
Document ID	EO-2E9C10C3CB
Generated	2026-08-06

Product Overview

25AMP 700V AC FERRULE 14.3 X 50.8MM

Eaton Bussmann series FWP high speed fuse, 700 Vac (UL), 700 Vdc (UL), 690 Vac (IEC), 25A, 200 kAIC at 700 Vac, 50 kAIC at 700 Vdc, Non Indicating, High speed fuse, Ferrule end X ferrule end, Class aR, White, Ceramic Fuse, Fuse-link, high speed, 25 A, AC 700 V, 14 x 51 mm, aR, UL, cylindrical, protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage starters, UL248, Breaking Capacity 200 kA, Optional accessories fuse-holder CH141B

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series High speed fuses

Additional Product Information

General specifications

Product Name Eaton Bussmann series high speed cylindrical fuse Catalog Number FWP-25A14F EAN 5027590500463
UPC 051712795951 Product Length/Depth 51 mm Product Height 15 mm Product Width 15 mm Product Weight 20.3 g
Compliances CE Marked

RoHS Compliant Certifications UL Recognized

CSA Certified Product specifications

Type High speed fuse Application Semiconductor, DC Common bus, DC drives, Power converters/rectifiers Amperage
Rating 25 A Accessories Breaking capacity 200 kA Frequency rating - max 62 Hz Frequency rating - min 45 Hz Fuse
indicator Non Indicating Release characteristic Other Utilization category aR (accompanied semiconductor protection)
Voltage type AC/DC Fuse size 14 x 51 mm Class Class aR Clearing (I2T) 320 Watt losses 7 W Fuse shape Cylindrical

Minimum melting 46.5 I2t (A2 sec) Pre arc (I2T) 49 Used with Finger safe holders/blocks and striker Color White Interrupt rating 200 kAIC Connection Ferrule end x ferrule end Construction size 14 mm x 51 mm Material Ceramic Packaging type Standard Quantity 10 Voltage rating 700 V Fuse type FWP-A14F ETIM for FWP-25A14F Circuit breakers and fuses (EC002704)

Feature Name

Feature Value

Model (EF000010)

Ceramic fuse

Size (EF000088)

14x51 mm

Voltage type (EF000187)

AC/DC

Rated current (EF000227)

25 A

Utilization category according to IEC 60269 (EF002572)

aR (accompanied semiconductor protection)

Type of fuse status indicator (EF004473)

Other

Release characteristic (EF000889)

Other

Power loss at rated cu...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / FWP-25A14F with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.