

INDUSTRIAL COMPONENT DATA

25KV 10A EXPULSION LINK 25KB10 EATON ELECTRIC Air fuse-link, medium voltage, 10 A, AC 36 kV, 50.8 x 565mm, b..

Brand: EATON - MOELLER | Manufacturer Part Number: 25KV 10A EXPULSION LINK



Manufacturer	EATON - MOELLER
MPN / Reference	25KV 10A EXPULSION LINK
Catalog number	25KB10
Category	Expulsion fuse-link, medium voltage
Minimum order	25 Pcs
Document ID	EO-B00901BF07
Generated	2026-08-06

Product Overview

Air fuse-link, medium voltage, 10 A, AC 36 kV, 50.8 x 565mm, back-up, BS, with striker, style 36 tag

25KV 10A EXPULSION LINK

Expulsion fuse-link, medium voltage, 10 A, AC 25 kV, 660 mm, ANSI, K fast, style B termination

Fuse, Expulsion fuse-link, medium voltage, 10 A, AC 25 kV, 660 mm, ANSI, K fast, fixed NEMA button head link, protection of transformer primary side, feeder, capacitor bank, ANSI C37-42, Breaking Capacity 8 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Busmann Series Medium Voltage fuses and accessories
--------------	---

Additional Product Information

General specifications

Product Name Eaton Busmann series medium voltage expulsion fuse Catalog Number 25KB10 EAN 5027590470230

UPC 051712398633 Product Length/Depth 225 mm Product Height 76 mm Product Width 106 mm Product Weight 17.76 g

Certifications ANSI/IEEE Std C37.42 Electrical data

Amperage Rating 10 A Voltage rating 25 kV Voltage type AC Current characteristic type Type K - Complies with ANSI C 37-42 requirements for fast acting K Characteristics Rated frequency - min 50 Hz Product specification

Construction size 660 mm Standard ANSI Type of termination Fixed buttonhead Color Yellow

ETIM for 25KB10 Circuit breakers and fuses (EC003611)

Feature Name

Feature Value

Rated current (EF000227)

10 A
Rated voltage (EF000228)
25 kV
Voltage type (EF000187)
AC
Rated frequency (EF001663)
50 Hz
Release characteristic (EF000889)
K
Type of termination (EF012540)
Fixed buttonhead
Standard (EF009322)
ANSI

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 25KV 10A EXPULSION LINK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.