

INDUSTRIAL COMPONENT DATA

25KV 15A EXPULSION LINK 25TB15 EATON ELECTRIC

Cartridge fuse, expulsion, MT, 15 A, AC 25 kV, 660 mm, ANSI a,..

Brand: EATON - MOELLER | Manufacturer Part Number: 25KV 15A EXPULSION LINK



Manufacturer	EATON - MOELLER
MPN / Reference	25KV 15A EXPULSION LINK
Catalog number	25TB15
Category	Expulsion fuse-link, medium voltage
Minimum order	25 Pcs
Document ID	EO-F482E61352
Generated	2026-08-06

Product Overview

Cartridge fuse, expulsion, MT, 15 A, AC 25 kV, 660 mm, ANSI a, T slow

25KV 15A EXPULSION LINK

Expulsion fuse-link, medium voltage, 15 A, AC 25 kV, 660 mm, ANSI, T slow, style B termination

Fuse, Expulsion fuse-link, medium voltage, 15 A, AC 25 kV, 660 mm, ANSI, T slow, fixed NEMA button head link, protection of transformer primary side, feeder, capacitor bank, ANSI C37-42, Breaking Capacity 8 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series Medium Voltage fuses and accessories

Additional Product Information

General specifications

Product Name Eaton Bussmann series medium voltage expulsion fuse Catalog Number 25TB15 EAN 5027590471282

Product Length/Depth 225 mm Product Height 76 mm Product Width 106 mm Product Weight 38.84 g Certifications

ANSI/IEEE Std C37.42 Electrical data

Amperage Rating 15 A Voltage rating 25 kV Voltage type AC Current characteristic type Type T - Complies with ANSI C 37-42 requirements for slow acting T characteristics Rated frequency - min 50 Hz Product specification

Construction size 660 mm Standard ANSI Type of termination Fixed buttonhead Color Green

ETIM for 25TB15 Circuit breakers and fuses (EC003611)

Feature Name

Feature Value

Rated current (EF000227)

15 A

Rated voltage (EF000228)

25 kV

Voltage type (EF000187)

AC

Rated frequency (EF001663)

50 Hz

Release characteristic (EF000889)

T

Type of termination (EF012540)

Fixed buttonhead

Standard (EF009322)

ANSI

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 25KV 15A EXPULSION LINK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.