

## INDUSTRIAL COMPONENT DATA

# 25KV 20AMP EXPULSION LINK 25TBR20 EATON ELECTRIC

## Expulsion fuse-link, medium voltage, 7.5 A, AC 15 kV, 533 m..

Brand: EATON - MOELLER | Manufacturer Part Number: 25KV 20AMP EXPULSION LINK



|                 |                                     |
|-----------------|-------------------------------------|
| Manufacturer    | EATON - MOELLER                     |
| MPN / Reference | 25KV 20AMP EXPULSION LINK           |
| Catalog number  | 25TBR20                             |
| Category        | Expulsion fuse-link, medium voltage |
| Minimum order   | 25 Pcs                              |
| Document ID     | EO-D0FEC8F715                       |
| Generated       | 2026-08-06                          |

### Product Overview

Expulsion fuse-link, medium voltage, 7.5 A, AC 15 kV, 533 mm, ANSI, K fast, style B termination

25KV 20AMP EXPULSION LINK

Expulsion fuse-link, medium voltage, 20 A, AC 25 kV, 660 mm, ANSI, T slow, style BR termination

Fuse, Expulsion fuse-link, medium voltage, 20 A, AC 25 kV, 660 mm, ANSI, T slow, fixed NEMA button head link, protection of transformer primary side, feeder, capacitor bank, ANSI C37-42, Breaking Capacity 8 kA

## STRUCTURED PRODUCT DATA

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path

EATON - MOELLER &gt; Busmann Series Medium Voltage fuses and accessories

### Additional Product Information

General specifications

Product Name Eaton Busmann series medium voltage expulsion fuse Catalog Number 25TBR20 EAN 5027590471466

Product Length/Depth 225 mm Product Height 76 mm Product Width 106 mm Product Weight 49.24 g Certifications

ANSI/IEEE Std C37.42 Electrical data

Amperage Rating 20 A Voltage rating 25 kV Voltage type AC Current characteristic type Type T - Complies with ANSI C 37-42 requirements for slow acting T characteristics Rated frequency - min 50 Hz Product specification

Construction size 660 mm Standard ANSI Type of termination Removable buttonhead Color Green

ETIM for 25TBR20 Circuit breakers and fuses (EC003611)

Feature Name

Feature Value

Rated current (EF000227)

20 A  
Rated voltage (EF000228)  
25 kV  
Voltage type (EF000187)  
AC  
Rated frequency (EF001663)  
50 Hz  
Release characteristic (EF000889)  
T  
Type of termination (EF012540)  
Removable buttonhead  
Standard (EF009322)  
ANSI

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 25KV 20AMP EXPULSION LINK with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.