

## INDUSTRIAL COMPONENT DATA

# 25KV 6A EXPULSION LINK 25KB6 EATON ELECTRIC

## Cartridge fuse, expulsion, MT, 6 A, AC 25 kV, 660 mm, ANSI a, K ..

Brand: EATON - MOELLER | Manufacturer Part Number: 25KV 6A EXPULSION LINK



|                 |                                     |
|-----------------|-------------------------------------|
| Manufacturer    | EATON - MOELLER                     |
| MPN / Reference | 25KV 6A EXPULSION LINK              |
| Catalog number  | 25KB6                               |
| Category        | Expulsion fuse-link, medium voltage |
| Minimum order   | 25 Pcs                              |
| Document ID     | EO-F688592671                       |
| Generated       | 2026-08-06                          |

### Product Overview

Cartridge fuse, expulsion, MT, 6 A, AC 25 kV, 660 mm, ANSI a, K fast

25KV 6A EXPULSION LINK

Expulsion fuse-link, medium voltage, 6 A, AC 25 kV, 660 mm, ANSI, K fast, style B termination

Fuse, Expulsion fuse-link, medium voltage, 6 A, AC 25 kV, 660 mm, ANSI, K fast, fixed NEMA button head link, protection of transformer primary side, feeder, capacitor bank, ANSI C37-42, Breaking Capacity 8 kA

## STRUCTURED PRODUCT DATA

### Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

### Classification & Catalog Path

Catalog path

EATON - MOELLER &gt; Bussmann Series Medium Voltage fuses and accessories

### Additional Product Information

General specifications

Product Name Eaton Bussmann series medium voltage expulsion fuse Catalog Number 25KB6 EAN 5027590470339 UPC 051712398619 Product Length/Depth 225 mm Product Height 76 mm Product Width 106 mm Product Weight 17.76 g

Certifications ANSI/IEEE Std C37.42 Electrical data

Amperage Rating 6 A Voltage rating 25 kV Voltage type AC Current characteristic type Type K - Complies with ANSI C 37-42 requirements for fast acting K Characteristics Rated frequency - min 50 Hz Product specification

Construction size 660 mm Standard ANSI Type of termination Fixed buttonhead Color Yellow

ETIM for 25KB6 Circuit breakers and fuses (EC003611)

Feature Name

**Feature Value**

Rated current (EF000227)

6 A

Rated voltage (EF000228)

25 kV

Voltage type (EF000187)

AC

Rated frequency (EF001663)

50 Hz

Release characteristic (EF000889)

K

Type of termination (EF012540)

Fixed buttonhead

Standard (EF009322)

ANSI

**REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW**

Send EATON - MOELLER / 25KV 6A EXPULSION LINK with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.