

INDUSTRIAL COMPONENT DATA

25KV 6A EXPULSION LINK 25TBR6 EATON ELECTRIC

Fuse-link, DII, 6A, 500 V, DZ

Brand: EATON - MOELLER | Manufacturer Part Number: 25KV 6A EXPULSION LINK



Manufacturer	EATON - MOELLER
MPN / Reference	25KV 6A EXPULSION LINK
Catalog number	25TBR6
Category	Expulsion fuse-link, medium voltage
Minimum order	25 Pcs
Document ID	EO-38B7F24DE8
Generated	2026-08-06

Product Overview

Fuse-link, DII, 6A, 500 V, DZ

25KV 6A EXPULSION LINK

Expulsion fuse-link, medium voltage, 6 A, AC 25 kV, 660 mm, ANSI, T slow, style BR termination

Fuse, Expulsion fuse-link, medium voltage, 6 A, AC 25 kV, 660 mm, ANSI, T slow, fixed NEMA button head link, protection of transformer primary side, feeder, capacitor bank, ANSI C37-42, Breaking Capacity 8 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path

EATON - MOELLER > Bussmann Series Medium Voltage fuses and accessories

Additional Product Information

General specifications

Product Name Eaton Bussmann series medium voltage expulsion fuse Catalog Number 25TBR6 EAN 5027590471589

Product Length/Depth 225 mm Product Height 76 mm Product Width 106 mm Product Weight 23.24 g Certifications

ANSI/IEEE Std C37.42 Product specifications

Type Medium Voltage Expulsion Fuse Link Application Primary side transformer protection, feeder protection, capacitor bank protection Amperage Rating 6 A Current characteristic type Type T - Complies with ANSI C 37-42 requirements for slow acting T characteristics Rated frequency - max 60 Hz Rated frequency - min 50 Hz Release characteristic T Standard ANSI Type of termination Removable buttonhead Voltage type AC Color Green Interrupt rating 8 kAIC Construction size 660 mm Voltage rating 25 kV

ETIM for 25TBR6 Circuit breakers and fuses (EC003611)

Feature Name

Feature Value

Rated current (EF000227)

6 A

Rated voltage (EF000228)

25 kV

Voltage type (EF000187)

AC

Rated frequency (EF001663)

50 Hz

Release characteristic (EF000889)

T

Type of termination (EF012540)

Removable buttonhead

Standard (EF009322)

ANSI

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 25KV 6A EXPULSION LINK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.