

INDUSTRIAL COMPONENT DATA

25KBR7.5 25KBR7-5 EATON ELECTRIC 25KV 7-5A REMOVABLE B/H EXPULSION LINK

Brand: EATON - MOELLER | Manufacturer Part Number: 25KBR7.5



Manufacturer	EATON - MOELLER
MPN / Reference	25KBR7.5
Catalog number	25KBR7-5
Category	Expulsion fuse-link, medium voltage
Minimum order	25 Pcs
Document ID	EO-50734252A8
Generated	2026-08-06

Product Overview

25KV 7-5A REMOVABLE B/H EXPULSION LINK

25KBR7.5 - Expulsion fuse-link, medium voltage, 7.5 A, AC 25 kV, 660 mm, ANSI, K fast

Fuse, Expulsion fuse-link, medium voltage, 7.5 A, AC 25 kV, 660 mm, ANSI, K fast, removable NEMA button head link, protection of transformer primary side, feeder, capacitor bank, ANSI C37-42, Breaking Capacity 8 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series Medium Voltage fuses and accessories

Additional Product Information

Expulsion fuse-link, medium voltage, 7.5 A, AC 25 kV, 660 mm, ANSI, K fast
Fuse, Expulsion fuse-link, medium voltage, 7.5 A, AC 25 kV, 660 mm, ANSI, K fast, removable NEMA button head link, protection of transformer primary side, feeder, capacitor bank, ANSI C37-42, Breaking Capacity 8 kA

General specifications
Product name Eaton Bussmann series medium voltage expulsion fuse
Part no. 25KV 7-5A
REMOVABLE B/H EXPULSION LINK
EAN 5027590470636
Product Length/Depth 225 millimetre
Product height 76 millimetre
Product width 106 millimetre
Product weight 26.2 gram
Compliances CE
Product Tradename None
Product Type Medium voltage expulsion fuse
Product Sub Type None
Electrical data
Amperage Rating 7.5 A
Voltage rating 25 kV
Current characteristic type Type K - Complies with ANSI C 37-42 requirements for fast acting K Characteristics
Rated frequency - min 50 Hz
Rated frequency - max 60 Hz
Product specifications
Application Primary side transformer protection, feeder protection, capacitor bank protection
Standard ANSI
Type of termination Removable buttonhead
Technical data ETIM 8.0
Circuit breakers and fuses (EG000020) / Expulsion fuse-link, medium voltage (EC003611)
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse systems / Safety fuse systems (unspecified) (Email

protected] [BAB265011])Rated current7.5 ARated voltage25 kVVoltage typeACRated frequency50 - 60 HzRelease
characteristicKType of terminationRemovable buttonheadStandardANSI
ETIM for 25KBR7.5 Circuit breake...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 25KBR7.5 with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.