

INDUSTRIAL COMPONENT DATA

25KV 7.5A EXPULSION LINK 25KB7.5 25KB7-5 EATON ELECTRIC Expulsion fuse-link, medium voltage, 7.5 A, AC 15 kV..

Brand: EATON - MOELLER | Manufacturer Part Number: 25KV 7.5A EXPULSION LINK



Manufacturer	EATON - MOELLER
MPN / Reference	25KV 7.5A EXPULSION LINK
Catalog number	25KB7-5
Category	Expulsion fuse-link, medium voltage
Minimum order	25 Pcs
Document ID	EO-E3965EFDBE
Generated	2026-08-06

Product Overview

Expulsion fuse-link, medium voltage, 7.5 A, AC 15 kV, 533 mm, ANSI, K fast, style B termination

25KV 7.5A EXPULSION LINK

25KV 7.5A EXPULSION LINK - Expulsion fuse-link, medium voltage, 7.5 A, AC 25 kV, 8 kA, 660 mm, ANSI, fixed NEMA button head link, K fast

Fuse, Expulsion fuse-link, medium voltage, 7.5 A, AC 25 kV, 660 mm, ANSI, K fast, fixed NEMA button head link, protection of transformer primary side, feeder, capacitor bank, ANSI C37-42, Breaking Capacity 8 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Busmann Series Medium Voltage fuses and accessories
--------------	---

Additional Product Information

Expulsion fuse-link, medium voltage, 7.5 A, AC 25 kV, 8 kA, 660 mm, ANSI, fixed NEMA button head link, K fast
Fuse, Expulsion fuse-link, medium voltage, 7.5 A, AC 25 kV, 660 mm, ANSI, K fast, fixed NEMA button head link, protection of transformer primary side, feeder, capacitor bank, ANSI C37-42, Breaking Capacity 8 kA
Delivery program
Product range FuseBasic function Expulsion fuse-linkField of application medium voltageRated current [I]
7.5 ARated voltage AC 25 kVSize 660 mmDescription fixed NEMA button head linkBreaking Capacity 8 kA
Usable for size/applications protection of transformer primary side, feeder, capacitor bankRelease characteristic [class]
K fastStandard/Approval ANSIStandards/Regulations ANSI C37-42Technical data ETIM 7.0
Circuit breakers and fuses (EG000020) / Expulsion fuse-link, medium voltage (EC003611)Rated current 7.5 ARated

voltage25000 VVoltage typeACRated frequency45 - 62 HzRelease characteristicKType of terminationFixed
buttonheadStandardANSI
ETIM for 25KB7.5 Circuit breakers and fuses (EC003611)
Feature Name
Feature Value
Rated current (EF000227)
7.5 A
Rated voltage (EF000228)
25 kV
Voltage type (EF000187)
AC
Rated frequency (EF001663)
50 Hz
Release characteristic (EF000889)
K
Type of termination (EF012540)
Fixed buttonhead
Standard (EF009322)
ANSI

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 25KV 7.5A EXPULSION LINK with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.