

INDUSTRIAL COMPONENT DATA

280A 690V AC TYPE T FUSE 280MMT EATON ELECTRIC cartridge fuse, ultra rapid, 280 A, AC 690 V, DC 350 V, BS88,...

Brand: EATON - MOELLER | Manufacturer Part Number: 280A 690V AC TYPE T FUSE



Manufacturer	EATON - MOELLER
MPN / Reference	280A 690V AC TYPE T FUSE
Catalog number	280MMT
Category	HRC fuse
Minimum order	1 Pcs
Document ID	EO-E49B0F5C6A
Generated	2026-08-06

Product Overview

cartridge fuse, ultra rapid, 280 A, AC 690 V, DC 350 V, BS88, 83 x 113 mm, aR, BS

280A 690V AC TYPE T FUSE

Eaton Busmann series high speed British standard fuse, Double barrel, 280A, 690 VAC/350 VDC (IEC), 700 VAC (UL), Class aR, Breaking capacity 200 kA RMS Sym., 40 kA DC at 350 VDC (IEC)

Fuse, Fuse-link, high speed, 280 A, AC 690 V, DC 350 V, BS88, 83 x 113 mm, aR, BS, centre bolted tags (dual barrel), protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage starters, BS88-4, IEC 60269-4, Breaking Capacity 200 kA, Optional accessories fuse-holder BH-3133

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Busmann Series High speed fuses

Additional Product Information

General specifications

Product Name Eaton Busmann series high speed british standard fuse Catalog Number 280MMT EAN 5027590039604
UPC 051712833394 Product Length/Depth 110 mm Product Height 83 mm Product Width 39 mm Product Weight 478 g

Compliances RoHS Compliant

CE Marked Product specifications

Type Fuse Application Semiconductor, DC Common bus, DC drives, power converters/rectifiers Amperage Rating 280 A
Breaking capacity 200 kA Fuse indicator None Insulated metal gripping lugs (IMGL) No Utilization category aR
(accompanied semiconductor protection) Voltage type AC/DC Rated switching capacity 200 kA Rated voltage AC 690 V
Rated voltage DC 350 V Center-to-center distance of connections 85 mm Mounting dimension M8 Current type AC/DC

Class Class aR Clearing (I2T) 47000 Watt losses 47 W Fuse shape Center dual barrel bolted tags Pre arc (I2T) 6600 Color None Interrupt rating 200 kA RMS Sym (IEC/UL), 40 kA at 350 Vdc (IEC) Connection Blade end x blade end Construction size Other Mounting method Stud Packaging type Standard Voltage rating 690 V (IEC), 700 V (UL) Fuse type MMT Suitable for MC-700 Trip indicator kit (indicator + clips)

TI700 Fuse indicator

MAI Microswitch/adaptor

MBI Microswitch/adaptor Fuse system (according to IEC 60269) Other

ETIM for 280MMT Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Other

Fuse construction type according to IEC 60269 (EF015865)

Other

Type of current (EF000143)

AC/DC

Rated volt...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 280A 690V AC TYPE T FUSE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.