

INDUSTRIAL COMPONENT DATA

2A 550V AC BS88 gG FUSE AAO2 EATON ELECTRIC

Fuse-link, LV, 40 A, AC 500 V, BS88, 21 x 129 mm, gL/gG, BS

Brand: EATON - MOELLER | Manufacturer Part Number: 2A 550V AC BS88 gG FUSE



Manufacturer	EATON - MOELLER
MPN / Reference	2A 550V AC BS88 gG FUSE
Catalog number	AAO2
Category	HRC fuse
Minimum order	20 Pcs
Document ID	EO-B03C97B1D2
Generated	2026-08-06

Product Overview

Fuse-link, LV, 40 A, AC 500 V, BS88, 21 x 129 mm, gL/gG, BS

2A 550V AC BS88 gG FUSE

Fuse-link, LV, 2 A, AC 550 V, BS88/A2, 14 x 85 mm, gL/gG, BS

Fuse, Fuse-link, low voltage, 2 A, AC 550 V, BS88/A2, 14 x 85 mm, gL/gG, BS, offset bolted tags, general industrial applications, BS88-2, IEC 60269-2, Breaking Capacity 80 kA, Optional accessories fuse-holder CM32F RS32

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Busmann Series Low Voltage fuses and accessories

Additional Product Information

General specifications

Product Name Eaton Busmann series low voltage british standard fuse Catalog Number AAO2 EAN 5027590422321 UPC 051712838405 Product Length/Depth 85 mm Product Height 14 mm Product Width 14 mm Product Weight 20.1 g

Compliances CE Marked

RoHS Compliant Certifications IEC 60269-2

BS88 Electrical data

Amperage Rating 2 A Voltage rating 550 V Voltage type AC Breaking capacity 80 kA Class Class gG/gL Compatible fuse holder

Suitable for CM32F Camaster fuse holder

RS32 Red spot fuse holder Product specifications

Fuse type AAO Fitted with: Offset bolted tags Construction BS88/A2

ETIM for AAO2 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Fuse system E

Fuse construction type according to IEC 60269 (EF015865)

A2

Type of current (EF000143)

AC

Rated voltage AC (EF007682)

550 V

Rated current (EF000227)

2 A

Utilization category according to IEC 60269 (EF002572)

gG (cable protection/equipment protection)

Breaking capacity (EF005617)

80 kA

Colour code (EF000931)

None

Type of fuse status indicator (EF004473)

None

Power loss at rated current (EF012389)

0.9 W

Mounting holes (EF021553)

M5

Centre-to-centre distance of connections (EF021151)

73 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 2A 550V AC BS88 gG FUSE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.