

## INDUSTRIAL COMPONENT DATA

# 2A INDR'L FUSE (10) 2HF36 EATON ELECTRIC Fuse-link, high speed, 2 A, AC 1200 V, DC 750 V, 22 x 102 mm, gL/gG..

Brand: EATON - MOELLER | Manufacturer Part Number: 2A INDR'L FUSE (10)



|                 |                     |
|-----------------|---------------------|
| Manufacturer    | EATON - MOELLER     |
| MPN / Reference | 2A INDR'L FUSE (10) |
| Catalog number  | 2HF36               |
| Category        | HRC fuse            |
| Minimum order   | 10 Pcs              |
| Document ID     | EO-B407291AF0       |
| Generated       | 2026-08-06          |

## Product Overview

Fuse-link, high speed, 2 A, AC 1200 V, DC 750 V, 22 x 102 mm, gL/gG, BS  
fuse cartridge, ultra-fast, 2 A, AC 1200 V, DC 750 V, 22 x 102 mm, gL/gG, BS  
Fuse, Fuse-link, high speed, 2 A, AC 1200 V, DC 750 V, 22 x 102 mm, gL/gG, BS, cylindrical, traction, BS, Breaking Capacity 80 kA

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                                     |
|--------------|---------------------------------------------------------------------|
| Catalog path | EATON - MOELLER > Bussmann Series Low Voltage fuses and accessories |
|--------------|---------------------------------------------------------------------|

## Additional Product Information

Fuse-link, high speed, 2 A, AC 1200 V, DC 750 V, 22 x 102 mm, gL/gG, BS Fuse, Fuse-link, high speed, 2 A, AC 1200 V, DC 750 V, 22 x 102 mm, gL/gG, BS, cylindrical, traction, BS, Breaking Capacity 80 kA [ Delivery program  
Product range Fuse Basic function Fuse-link Field of application high speed Rated current [I] 2 A Rated voltage AC 1200 V DC 750 V Size 22 x 102 mm Utilization category gL/gG Breaking Capacity 80 kA usable for size/applications traction  
Standard/Approval BS Shape cylindrical Standards/Regulations BS , Technical data ETIM 7.0  
Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse ([email protected]) [AFZ800015]) Construction size Other Rated current 2 A Rated voltage 1200 V Voltage type AC/DC Rated switching capacity 80 kA Utilization category gL/gG (cable protection/equipment protection) Type of fuse status indicator None Insulated metal gripping lugs (IMGL) No ]  
ETIM for 2HF36 Circuit breakers and fuses (EC004556)  
Feature Name

**Feature Value**

Fuse system according to IEC 60269 (EF017676)

Other

Fuse construction type according to IEC 60269 (EF015865)

Other

Type of current (EF000143)

AC/DC

Rated voltage AC (EF007682)

1200 V

Rated voltage DC (EF012281)

750 V

Rated current (EF000227)

2 A

Utilization category according to IEC 60269 (EF002572)

gG (cable protection/equipment protection)

Breaking capacity (EF0056...)

**REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW**

Send EATON - MOELLER / 2A INDR'L FUSE (10) with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.