

INDUSTRIAL COMPONENT DATA

2AMP 550V AC BS88 FUSE NSD2 EATON ELECTRIC

Fuse-holder, low voltage, 32 A, AC 550 V, BS88/F1, 1P, BS, back s..

Brand: EATON - MOELLER | Manufacturer Part Number: 2AMP 550V AC BS88 FUSE



Manufacturer	EATON - MOELLER
MPN / Reference	2AMP 550V AC BS88 FUSE
Catalog number	NSD2
Category	HRC fuse
Minimum order	20 Pcs
Document ID	EO-3F3B570A0C
Generated	2026-08-06

Product Overview

Fuse-holder, low voltage, 32 A, AC 550 V, BS88/F1, 1P, BS, back stud unit, white

2A, AC 550 V, V88/F1, 14 x 59 mm LV Fuse

Fuse-link, low voltage, 2 A, AC 550 V, 80 kA, BS88/F1, 14 x 59 mm, gL/gG, BS

Fuse, Fuse-link, low voltage, 2 A, AC 550 V, BS88/F1, 14 x 59 mm, gL/gG, BS, offset bladed tags, general industrial applications, BS88-2, IEC 60269-2, Breaking Capacity 80 kA, Optional accessories fuse-holder 32NNS SC32

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Bussmann Series Low Voltage fuses and accessories

Additional Product Information

Fuse-link, low voltage, 2 A, AC 550 V, 80 kA, BS88/F1, 14 x 59 mm, gL/gG, BSFuse, Fuse-link, low voltage, 2 A, AC 550 V, BS88/F1, 14 x 59 mm, gL/gG, BS, offset bladed tags, general industrial applications, BS88-2, IEC 60269-2, Breaking Capacity 80 kA, Optional accessories fuse-holder 32NNS SC32Delivery program

Product rangeFuseBasic functionFuse-linkField of applicationlow voltageRated current [I]₂ ARated voltageAC 550

VConstruction sizeBS88/F1Size14 x 59 mmUtilization categorygL/gGBreaking Capacity80 kAusable for

size/applicationsgeneral industrial applicationsStandard/ApprovalBSShapeoffset bladed tagsStandards/RegulationsBS88-2

IEC 60269-2Optional accessoriesfuse-holder 32NNS and SC32Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse ()

[AFZ800015])Construction sizeOtherRated current2 ARated voltage550 VVoltage typeACRated switching capacity80 kAUtilization categorygL/gG (cable protection/equipment protection)Type of fuse status indicatorNoneInsulated metal gripping lugs (IMGL)No

ETIM for NSD2 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Fuse system E

Fuse construction type according to IEC 60269 (EF015865)

F1

Type of current (EF000143)

AC

Rated voltage AC (EF007682)

550 V

Rated current (EF000227)

2 A

Utilizati...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / 2AMP 550V AC BS88 FUSE with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.